

6 In. 15W (32W Replacement) Selectable White G13 Base (T8 Or T8 And T12 Replacement) U-Bend Linear LED Tube

Features

- Two installation options: plug and play direct replacement or ballast bypass
- Shatter-resistant and mercury-free, no special disposal is required
- Flicker-free, instant ON illumination at full brightness
- **Ideal usage:** General Purpose Lighting



Specifications

Item Number	Item Length (In)	Item Width (In)	Bulb Shape
T848/3CCT/U6/LED	22.7	6.9	T8
Bulb Type	Bulb Base	Bulb Finish	Tube Type
Tubular	G13	White	Type A/B
Technology	Brightness (LUMENS)	Lumen Efficiency (LPW)	Color Accuracy (CRI)
Led - Smd	2100	140.0	80
Color Temperature (CCT)	Life Hours	Life Years	Voltage (V)
3000 4000 6500	50000	45.7	120-277
Replacement (Wattage)	Annual Energy Cost (\$)	Energy Efficiency	Energy Used (Wattage)
32	1.81	53.1%	15
Battery Operated	Pack Quantity	Smart	Portable
No	1	No	No
Dimmable	Hardwire	Enclosed Fixture Rated	Safety Location
No	No	No	Damp
CEC Compliant			
Not Regulated			