

This Is An Original Product From Fulham Co., Inc

Description: RACEHORSE Series, Universal Operating Voltage, Program Preheat Start Ballast, End Of Life Protection, Auto Restart, Cold Starting Feature.

This Ballast Will Operate Following Lamps.


F24T5HO/F39T5HO


TWIN(FT/E), 4 PIN 24/40/36W



ELECTRICAL DATA (With 120 Volt Application)

INPUT VOLT: 120V ± 10%,	50/60Hz									_
LAMP WATTS/TYPE	F39T5HO	F24T5HO	T5CR40W	T5CR22W	FT36W	FT24W	FT40W	-	-	
LAMPS OPERATED	1									
INPUT WATTS	43	29	42	29	36	29	50			
LINE CURRENT:	0.36	0.25	0.35	0.24	0.30	0.24	0.42			
POWER FACTOR		0.98 Type								
BALLAST FACTOR		1.0 +								
EFFICACY FACTOR	2.37	3.86	2.19	3.86	2.67	3.86	2.20			
THD	10.0%	10.0%	10.0%	10.0%	10.0%	10.0%	10.0%			
CURRENT CREST FACTOR		< 1.7								
EMI/RFI COMPLIANCE		FCC PART 18-A								
SOUND RATING		" A "								
BALLAST TYPE				PROGRA	AMMED STA	ART				
VOLTAGE TRANSIENTS		ANSI 62.41								
OUTPUT/PROTECTION		EOL								
COMPLIANCE		RoHS								
APPROVED		?????/								
MIN. OPERATING TEMP	-18 °C (0 °F)									
MAX. CASE TEMP	90 °C (194 ° F) SEE FOOT NOTE WARRANTY									
APPROVALS/CLASS	UL /cUL LISTED, CLASS " P ", 1 OUTDOOR									
REMOTE MOUNTING	18 FT MAX.									







This Is An Original Product From Fulham Co., Inc

Description: RACEHORSE Series, Universal Operating Voltage, Program Preheat Start Ballast, End Of Life Protection, Auto Restart, Cold Starting Feature.

This Ballast Will Operate Following Lamps.


F24T5HO/F39T5HO


TWIN(FT/E), 4 PIN 24/40/36W



ELECTRICAL DATA (With 120 Volt Application)

INPUT VOLT: 120V ± 10%,	50/60Hz								
LAMP WATTS/TYPE	F39T5HO	F24T5HO	T5CR40W	T5CR22W	FT36W	FT24W	T5CR22W + T5CR40W		
LAMPS OPERATED		1 EACH							
INPUT WATTS	87	55	80	54	69	54	68		
LINE CURRENT:	0.73	0.47	0.68	0.46	0.59	0.46	0.58		
POWER FACTOR	0.98 Type								
BALLAST FACTOR	1.0 +								
EFFICACY FACTOR	1.15	2.00	1.13	2.04	1.36	2.04	1.47		
THD	10.0%	10.0%	10.0%	10.0%	10.0%	10.0%	10.0%		
CURRENT CREST FACTOR		< 1.7							
EMI/RFI COMPLIANCE		FCC PART 18-A							
SOUND RATING		" A "							
BALLAST TYPE		PROGRAMMED START							
VOLTAGE TRANSIENTS		ANSI 62.41							
OUTPUT/PROTECTION		EOL							
COMPLIANCE	RoHS								
APPROVED	?????/								
MIN. OPERATING TEMP	-18 °C (0 °F)								
MAX. CASE TEMP	$90^{0}\mathrm{C}$ ($194^{0}\mathrm{F}$) SEE FOOT NOTE WARRANTY								
APPROVALS/CLASS	UL /cUL LISTED, CLASS " P ", 1 OUTDOOR								
REMOTE MOUNTING	18 FT MAX.								







This Is An Original Product From Fulham Co., Inc

Description: RACEHORSE Series, Universal Operating Voltage, Program Preheat Start Ballast, End Of Life Protection, Auto Restart, Cold Starting Feature.

This Ballast Will Operate Following Lamps.


F24T5HO/F39T5HO TWIN


TWIN(FT/E), 4 PIN 24/40/36W



ELECTRICAL DATA (With 277 Volt Application)

INPUT VOLT: 277V ± 10%,	50/60Hz									
LAMP WATTS/TYPE	F39T5HO	F24T5HO	T5CR40W	T5CR22W	FT36W	FT24W	FT40W	-	-	
LAMPS OPERATED	1									
INPUT WATTS	43	29/	42	29	36	29	50			
LINE CURRENT:	0.16	0.12	0.16	0.12	0.20	0.12	0.19			
POWER FACTOR	0.98 Type									
BALLAST FACTOR	1.0 +									
EFFICACY FACTOR	2.37	3.86	2.19	3.86	2.67	3.86	2.20			
THD	10.0%	10.0%	10.0%	10.0%	10.0%	10.0%	10.0%			
CURRENT CREST FACTOR	< 1.7									
EMI/RFI COMPLIANCE	FCC PART 18-A									
SOUND RATING		" A "								
BALLAST TYPE		PROGRAMMED START								
VOLTAGE TRANSIENTS				1A	NSI 62.41					
OUTPUT/PROTECTION		EOL								
COMPLIANCE		RoHS								
APPROVED		?????/								
MIN. OPERATING TEMP	-18 °C (0 °F)									
MAX. CASE TEMP	90 °C (194 °F) SEE FOOT NOTE WARRANTY									
APPROVALS/CLASS	UL /cUL LISTED, CLASS " P ", 1 OUTDOOR									
REMOTE MOUNTING	18 FT MAX.									







This Is An Original Product From Fulham Co., Inc

Description: RACEHORSE Series, Universal Operating Voltage, Program Preheat Start Ballast, End Of Life Protection, Auto Restart, Cold Starting Feature.

This Ballast Will Operate Following Lamps.

F24T5HO/F39T5HO

TWIN(FT/E), 4 PIN 24/40/36W



ELECTRICAL DATA (With 277 Volt Application)

INPUT VOLT: 277V ± 10%,	50/60Hz								
LAMP WATTS/TYPE	F39T5HO	F24T5HO	T5CR40W	T5CR22W	FT36W	FT24W	T5CR22W + T5CR40W		
LAMPS OPERATED			1 EACH						
INPUT WATTS	85	55	80	54	69	54	68		
LINE CURRENT:	0.31	0.21	0.29	0.20	0.25	0.20	0.25		
POWER FACTOR	0.98 Type								
BALLAST FACTOR	1.0 +								
EFFICACY FACTOR	1.18	2.00	1.13	2.04	1.36	2.04	1.47		
THD	10.0%	10.0%	10.0%	10.0%	10.0%	10.0%	10.0%		
CURRENT CREST FACTOR	< 1.7								
EMI/RFI COMPLIANCE	FCC PART 18-A								
SOUND RATING	"A"								
BALLAST TYPE		PROGRAMMED START							
VOLTAGE TRANSIENTS		ANSI 62.41							
OUTPUT/PROTECTION	EOL								
COMPLIANCE	RoHS								
APPROVED	?????/								
MIN. OPERATING TEMP	-18 °C (0 °F)								
MAX. CASE TEMP	90 °C (194 °F) SEE FOOT NOTE WARRANTY								
APPROVALS/CLASS	UL /cUL LISTED, CLASS " P ", 1 OUTDOOR								
REMOTE MOUNTING	18 FT MAX.								

