Project Name:	Type:
Part Number:	Date:



# ADJUSTAPAR LAMPS

## **FEATURES**

- The lamp is equipped with built-in switches that allow users to select from 5 different color temperatures and 2 beam angles, all in one convenient design
- Suitable to replace 75W and 120W halogen lamps
- Innovative optic lens design delivers even light without shadowing
- 5 field selectable color temperatures in 2700K, 3000K, 3500K, 4000K, and 5000K
- 2 field selectable light distributions in narrow flood 25° and flood 40° beam angles
- High CRI 90 for great color accuracy
- California Title 20 regulation compliant
- Available in PAR30, PAR30 short neck, and PAR38 form factors
- PAR30 short neck and PAR38 models are compatible with **GREEN CREATIVE SOL Gimbal Track Head**

#### https://greencreative.com/product-tag/sol/

- Smooth dimming with existing dimmers\*
- Compact size 1:1 halogen form factor
- Suitable for damp locations and totally enclosed fixtures
- Fixture operating temperature: -4°F to 95°F (-20°C to 35°C)
- Lamp ambient temperature: -4°F to 113°F (-20°C to 45°C)
- Rated Lifetime (L70): 25,000hrs
- 3 year limited warranty\*\*















## **FOCUS FEATURE**


## 2 Selectable Beam Angles







## **5 Selectable Color Temperatures**





3000K







WARM WHITE LIGHT

NEUTRAL WHITE LIGHT

COOL WHITE LIGHT

5000K DAY LIGHT

## **Compatible with SOL Gimbal Track Head**



The SOL Gimbal track head is designed with E26 medium base and compatible with both H-Type and J-Type adapters for seamlessly integrating with a variety of track rails.

Learn more about SOL Gimbal Track Head https://greencreative.com/product-tag/sol/




# **ADJUSTAPAR LAMPS**


SPE	CIFICATIONS														
Product	Model	Equiv.	Wattage (W)	5 Selectable CCTs	Lumens	Efficacy (LPW)	Input Voltage	2 Selectable Beam Angles	CBCP (cd)	CRI	Dim.*	Power Factor (typ.)	Fixture Rating	T20	DOE
37220	9PAR30DIM/9CCTS/BAS	75W	9	27K / 30K / 35K / 40K / 50K	810	90	120V	25° / 40°	2,510 / 1,315	90	Yes	0.9	Enclosed	1	J
37221	9PAR30SNDIM/9CCTS/BAS	75W	9	27K / 30K / 35K / 40K / 50K	810	90	120V	25° / 40°	2,510 / 1,315	90	Yes	0.9	Enclosed	1	J
37222	14PAR38DIM/9CCTS/BAS	120W	14	27K / 30K / 35K / 40K / 50K	1,350	96	120V	25° / 40°	4,300 / 2,235	90	Yes	0.9	Enclosed	1	J

<sup>\*</sup>This lamp is available for dimming with 120V line voltage only and might not be compatible with all dimmers. Please visit www.greencreative.com for compatibility information.

## **DIMENSION & WEIGHT**









Model	Model	Base	MOL	Dia.	Weight
37220	9PAR30DIM/9CCTS/BAS	E26	4-5/8"	3-3/4"	0.23 lb
37221	9PAR30SNDIM/9CCTS/BAS	E26	3-9/16"	3-3/4"	0.25 lb
37222	14PAR38DIM/9CCTS/BAS	E26	5-3/16"	4-3/4"	0.39 lb

## **ILLUMINANCE & CANDELA DISTRIBUTION**

## 9PAR30DIM/9CCTS/BAS 25° 2700K





Diameter	Footcandles
1.3	1,753
2.7	406
4.0	185
5.3	105
6.7	66



Degree	Candela
10	1,937
20	648
30	216
40	92
50	49

## 9PAR30DIM/9CCTS/BAS 40° 2700K





\	Diameter	1 Cottouridies
3'	2.2	308
6'	4.4	77
9'	6.6	34
12'	8.7	20
15	10.9	13

Diameter Footcandle


<sup>\*\*</sup>Please visit www.greencreative.com for Limited Warranty terms.




# **ADJUSTAPAR LAMPS**

# ILLUMINANCE & CANDELA DISTRIBUTIOIN

## 9PAR30SNDIM/9CCTS/BAS 25° 2700K




Diameter	Footcandles
1.3	1,761
2.7	408
4.0	186
5.3	106
6.7	66




Degree	Candela
10	1,990
20	651
30	208
40	86
50	46

### 9PAR30SNDIM/9CCTS/BAS 40° 2700K




Diameter	Footcandles
2.2	292
4.4	73
6.6	32
8.7	19
10.9	12




Degree	Candela
10	1,222
20	718
30	325
40	172
50	84

### 14PAR38DIM/9CCTS/BAS 25° 2700K




Diameter	Footcandles
1.3	2,529
2.7	586
4.0	267
5.3	152
6.7	95




Degree	Candela
10	3,011
20	1,077
30	346
40	144
50	75

### 14PAR38DIM/9CCTS/BAS 40° 2700K



Diameter	Footcandles			
2.2	485			
4.4	121			
6.6	54			
8.7	31			
10.9	20			



Degree	Candela			
10	2,045			
20	1,265			
30	535			
40	225			
50	103			

ORDERING INFORMATION									
Model -	Master Carton			Shipping Carton					
	Case Qty	Case Dimensions (LxWxH)	Case Weight	Case Qty	Case Dimensions (LxWxH)	Case Weight			
9PAR30DIM/9CCTS/BAS	6PCS	12-7/16" x 8-1/4" x 5-1/2"	2.34 lb	24PCS	17-5/16" x 13" x 12"	11.6 lb			
9PAR30SNDIM/9CCTS/BAS	6PCS	12-7/16" x 8-1/4" x 4-3/8"	2.31 lb	24PCS	17-5/16" x 13" x 9-11/16"	10.32 lb			
14PAR38DIM/9CCTS/BAS	6PCS	17-5/16" x 11-5/8" x 6-1/8"	4.63 lb	24PCS	24" x 17-15/16" x 13-3/8"	20.72 lb			

Note: All rights reserved. All sizes and specifications are subject to change at any time without notice.