

Linear Fluorescent Lampholders for Today's Energy-Efficient Lighting Fixtures



T-8 and T-5 Linear Fluorescent Lampholders

Leviton's new line of bi-pin fluorescent lampholders offer manufacturers a wealth of opportunities to incorporate energy-efficient lamps into their fixtures. With industry-leading wiring and mounting options, our miniature and medium bi-pin lampholders provide fast, easy assembly for a wide variety of streamlined, energy-efficient designs. From decorative and architectural lighting to ceiling lighting in virtually any commercial environment, Leviton's new lampholders "cover all the bases." We've been meeting the needs of OEMs for 100 years, always leading the industry with innovative products built to the highest quality and performance standards.

Medium Bi-Pin Lampholders for T-8 Lamps with G13 Base



New Selection Offers Total Design Flexibility

- Tall, Medium and Short Profile
- Bottom Wiring
- Slide-On or Snap-In Mounting

Applications:

- Ceiling lighting in a wide range of commercial environments including offices, schools, hotels and libraries
- Troffers and shop fixtures

Features and Benefits:

- Available in tall profile (30mm lamp center), medium profile (23mm lamp center) and new short profile (16mm lamp center)
- Bottom-load wiring
- Four-position, positive-stop lamp-lock socket for easy relamping in service
- Available with internal shunt connection for instant start ballasts or non-shunted versions
- Chemical-resistant white thermoplastic body
- Slide-On models fit thin 22 gauge panels for streamlined fixture designs
- Knife-edge contacts on Tall and Medium Slide-On models
- Snap-In models available with optional locator pin for added stability



Rating:

660W-600V

Agency Standards:

UL Listed  us (File #E-5833)
 NOM Certified (File #057)
 VDE Certified to IEC

ORDERING INFORMATION:	
Cat. No.	Description
13660-SL	Tall Profile Slide-On, 30mm lamp center height
23660-SL	Same as above, except with internal shunt connection
13661-SL	Medium Profile Slide-On, 23mm lamp center height
23661-SL	Same as above, except with internal shunt connection
13662-SL	Short Profile Slide-On, 16mm lamp center height
23662-SL	Same as above, except with internal shunt connection
13660-SWP	Tall Profile Snap-In with locator pin, 30mm lamp center height
13660-SNP	Same as above, except without locator pin
23660-SWP	Tall Profile Snap-In with locator pin and internal shunt connection, 30mm lamp center height
23660-SNP	Same as above, except without locator pin
13661-SWP	Medium Profile Snap-In with locator pin, 23mm lamp center height
13661-SNP	Same as above, except without locator pin
23661-SWP	Medium Profile Snap-In with locator pin and internal shunt connection, 23mm lamp center height
23661-SNP	Same as above, except without locator pin
13662-SWP	Short Profile Snap-In with locator pin, 16mm lamp center height
13662-SNP	Same as above, except without locator pin
23662-SWP	Short Profile Snap-In with locator pin and internal shunt connection, 16mm lamp center height
23662-SNP	Same as above, except without locator pin