

### **Morris CAT#: 71453C**


# LED Classic Full Cutoff Medium Wallpack












#### **Features:**

- Use in general lighting applications: Parking Lots
  & Building Security
- LumiLED LUXEON 3030 LEDs
- Die Cast Aluminum Housing
- Polyester Powder Coat Finish
- Housing Color: Bronze
- High Quality Tempered Glass Lens

- 4 Threaded K/Os -(1)Top, (1)Back, (2)Sides
- Photocontrol (not included) can be installed on fixture
- Stainless Steel Hardware
- Operation Temperature: -4°F to 104°F
- Voltage: 120/208/240/277V
- cETLus listed for Wet Locations
- DLC PRODUCT ID#: PLRR1H088GS8
- 5 Year Warranty

Part#	Input/ Wattage	Volts	Lumens	ССТ	CRI	Dimming	Light Pattern	Lumens/ Watt	DLC PRODUCT ID#:
71453C	45	120-277	4,598	5000K	>72	N/A	H113° V114.5°	102	PLRR1H088GS8

#### **Photometry:**





## **Morris CAT#: 71453C LED Classic Full Cutoff Medium Wallpacks** 120-277V, 5000K, 45W

**Electrical:** 

Input Voltage: 120V-277V

Current: 0.47@ 120V

Frequency: 50/60Hz

Power Factor: ≥.90

THD: <20% @120V

**Product Parameters:** 

Efficacy: 102 lumens per watt

50,000+ Hour L70 Life Span

CCT: 5000K (Cool White)

**Chromacity Measurements:** 

Beam Angle: H 113° V114.5°

BUG Rating: B3-U3-G2

CRI: 72

R9: -12

**Component Specifications:** 

LED: Lumileds 3030

120V-277V

50-60HZ

Driver Output Volts: 50-70V

Driver Output Amps: 1200mA

**4KV Surge Protection** 

Dimming: 0-10V

**Operating Temperature:** -4°F - 131°F

Construction:

Housing: Die Cast Aluminum Alloy

Whte Powder Coated Finish

Lens Material: Prismatic Borosilicate Glass Lens

**UV** Resistant Fire Resistant

IP Rating: IP54 suitable for wet locations

**Mounting:** Wall Mount

Listings:

cETLus

DLC PRODUCT ID#: PLRR1H088GS8

Accessory:

Emergency Backup - CAT#: 71465B

Warranty:

Morris Products carries a 5 year warranty from date of purchase against defects in materials and workmanship (assuming normal

and proper usage).