



MASTER GLASS LED candles and lustres



MAS LEDCandleDT2.5-25W E14 B35 CL G

Featuring a classic heritage design, Classic filament LED Lamps combine the familiar shapes of incandescent candles and lustres with the benefits of the long-lasting LED technology. It is an idea product to provide customers with cosy atmosphere. The MASTER LED candles and lustres can be dimmed for different lumen level and also for the different colour temperature. MASTER Glass Led Bulbs deliver significant energy savings, offering even 30% more compared to normal LED. They provide excellent quality of light. By offering a lifetime of 25,000 hours, the lamps reduce maintenance costs.

Product data


General information		LLMF at end of nominal lifetime (nom.)	
Cap base	E14 [E14]		70 %
CE mark	Yes	Operating and electrical	
EU RoHS compliant	Yes	Input frequency	50 to 60 Hz
Nominal lifetime (nom.)	25000 h	Power (Rated) (Nom)	2.5 W
Switching cycle	20,000X	Lamp current (nom.)	15 mA
	Sphere	Wattage equivalent	25 W
Tier	MASTER	Starting time (nom.)	0.5 s
Light technical		Warm-up time to 60% light (nom.)	0.5 s
Colour Code	922-927 [CCT of 2,200 K-2,700 K]	Power factor (nom.)	0.6
Luminous flux (nom.)	340 lm	Voltage (Nom)	220-240 V
Colour designation	Warm Glow (WG)	Temperature	
Correlated Colour Temperature (Nom)	2200 2700 K	T-ambient (max.)	45 °C
Luminous efficacy (rated) (nom.)	136 lm/W	T-ambient (min.)	-20 °C
Colour consistency	<6	T-Case maximum (nom.)	70 °C
Colour rendering index (nom.)	90		

MASTER GLASS LED candles and lustres

Controls and dimming	
Dimmable	Only with specific dimmers
Mechanical and housing	
Lamp Finish	Clear
Bulb material	Glass
Bulb shape	B35 [B 35mm]
Approval and application	
Energy Efficiency Class	D
Energy consumption kWh/1,000 hours	3 kWh
	1109136

Product data	
Full product code	871951444935000
Order product name	MAS LEDCandleDT2.5-25W E14 B35 CL G
EAN/UPC – product	8719514449350
Order code	44935000
SAP numerator – quantity per pack	1
Numerator – packs per outer box	10
SAP material	929003011982
Net Weight (Piece)	0.013 kg


Dimensional drawing




MAS LEDCandleDT2.5-25W E14 B35 CL G

Product	D	C
MAS LEDCandleDT2.5-25W E14 B35 CL G	35 mm	97 mm

Photometric data




General uniform lighting



Light Distribution Diagram


MASTER GLASS LED candles and lustres

Photometric data




Spectral Power Distribution Colour

Lifetime



Life Expectancy Diagram



Lumen Maintenance Diagram

