



e-Vision Low Wattage 20-150W

E-VISION RMH20KBLSM

Low frequency electronic HID ballasts such as the Philips Advance e-Vision line constantly measure and adjust the wattage, optimizing delivery of the ceramic lamps' superior color properties. This makes ceramic metal halide operated by e-Vision ballasts the premier choice for many applications previously illuminated by either tungsten halogen or incandescent sources, such as retail lighting.

Product data

General Information					
ANSI Code	C175				
Lamp Type	22W Philips Mini MC				
Number Of Lamps	1 piece/unit				
Ballast Type	Electronic HID				
Base Model	RMH20KBLS				
Suitable For Outdoor Use	Yes				
Operating and Electrical					
Input Voltage	120 V				
Input Frequency	50 to 60 Hz				
Total Harmonic Distortion USA	15 %				
Crestfactor (Nom)	1.8				
Ignition Time (Nom)	1200 s				
Ballast Factor (Nom)	1				
Power Factor (Nom)	0.90				
Input Current (Max)	0.23 A				
Input Current (Min)	0.23 A				

26 W				
22 W				
No terminals				
No terminals				
0.50 mm				
NA				
All leads = 6"				
18AWG mm				
Stranded				
Yes				
No				
No				
No connector				


Datasheet, 2016, February 1 data subject to change

e-Vision Low Wattage 20-150W

Temperature	
T-Case Maximum (Nom)	90 °C
Mechanical and Housing	
Housing Material	Metal
Housing	К
Housing Dimensions	4.1" x 1.3" x 1.2"
Approval and Application	
EMC Immunity Standard	FCC Non-Consumer
Approval Marks	CSA certificate UL certificate RoHS Compliant
Hum And Noise Level	A

UL Recognized	No	
Product Data		
Order product name	E-VISION RMH20KBLSM	
EAN/UPC - Product	781087092026	
Order code	913701221502	
Numerator - Quantity Per Pack	1	
Numerator - Packs per outer box	12	
Material Nr. (12NC)	913701221502	
Net Weight (Piece)	178.000 g	

Dimensional drawing



Product	A1	A2	A3	B1	B2	C1
E-VISION RMH20KBLSM	4.4 in	4.1 in	4.5 in	1.1 in	0.5 in	1.2 in

