

Project Name

Location

Prepared By



SATCO S21428

7CFL/L/840/G24D/AB/FR/U

Notes

(revised) 10-10-2023 00:17:35

General

Status	Active
Watts	7W
Fluorescent Equivalent	13W/18W/26W
Volts	120V-277V
Ballast Type	Type A/B
Shape	PL
Base	G24d (2-Pin)
ANSI Base	G24d
Finish	Frost
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80+
Lumens	910L
Beam Spread	300
Dimmable	Non-Dimmable
Hours Rated	50000
Operating Position	Universal
Technology	LED

Electrical

Operating Frequency	50/60Hz
Power Factor	0.9
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical

MOL	4.53
MOD	1.52
Housing Color	White
Weight (lb.)	0.14

Additional Information

Rated For Enclosed Fixture	Yes
Warranty	5-Years

Compliance

Safety Listing	cULus - Listed; cULus - Classified
Location Rating	Damp
DLC Approved	No
NSF Approved	Yes
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp