

Project Name

Location

Prepared By



SATCO S21916

11T8/LED/36/5CCT/DR

Notes

(revised) 12-22-2024 23:16:34

General

Status	Active
Watts	11W
Fluorescent Equivalent	25W
Volts	Ballast Dependent
Ballast Type	Type A
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	36
Finish	Frost
CCT (Kelvin)	3000K/3500K/4000K/5000K/6500K
Temperature	Soft White to Daylight
CRI	83
Lumens	1650L/1700L/1750L/1750L/1700L
Beam Spread	220
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED

Electrical

Ballasting Requirements	Ballast required, check compatibility
Operating Frequency	50/60Hz
Dimming Type	Phase cut
Dimming Note	Only in Type A mode; Check Ballast MFG for Dimmer Compatibility
Power Factor	>0.9
THD	<20%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical

MOL	35.78
MOD	1
Material	Glass
Weight (lb.)	0.34

Additional Information

Shatter-Proof Type	PET Coated
Rated For Enclosed Fixture	Yes
Warranty	5 Year Limited - T8 LED Bulbs

Compliance

Safety Listing	cULus - Certified; cULus - Listed
Location Rating	Damp
DLC Approved	Yes
DLC ID	S-D6LTLD
CA T20 / T24 Rationale	Exempt - Base Not Regulated
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes