



Project / Job Name:

Location:

Fixture Type:

Notes:

S26500 - 16 Watt T12 LED; 3K/4K/5K/65K CCT
Selectable; G13 Base; 2-Pack



GENERAL

Company	SATCO
EA Height	1.69
EA Width	2.99
EA Length	47.87
Lamp Ballast Type AB	Type A
Ballasting Requirements	Ballast required, check compatibility
Dimmable Text	Only Dimmable with Compatible Dimming Ballasts
Lamp Filament	LED
Material	Glass
Product Notes	Not for use in vapor tight fixtures.
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 1KV
Total Harmonic Distortion	<25%
CCT Selectable	True
Wattage Selectable	False
Finish Family	White
Amps	0.133-0.058A
Has Camera	False
IOT Enabled	False
Leg Spacing	0.51
Power Factor	0.9
SDS Class	LED_Lamp
Shatter Proof Type	PET Coated
Indoor Outdoor	Indoor
Product Technology	LED
Fluor Equiv	40W

ELECTRICAL

CCT (Kelvin Temp)	3000K/4000K/5000K/6500K
Dimmable	Yes-Dimmable
Hours Rated	36000
Beam Angle (degree)	240
Color Temp	Soft White to Daylight
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	1700L/1700L/1800L/1800L
Volts	Ballast Dependent
Watts	16W

PHYSICAL

Lamp Base	Medium Bi Pin
Finish	Frost
Housing Color	White
ANSI Base	G13
Lamp Type	T12
MOD Lamps	1.42
MOL	47.74

ADDITIONAL INFO

Warranty	3-Years
Rated For Enclosed Fixture	False

FEATURES

Flicker Free	False
--------------	-------

PACKAGING

UPC	045923265006
Case Cube	0.9363
Case Height	5.35
Case Length	48.62
Case Quantity	6
Case UPC	10045923265003
Case Weight	10.95
Case Width	6.22
EA Cube	0.14
EA Height	1.69
EA Length	47.87
EA Quantity	1
EA Weight	1.7
EA Width	2.99
Inner Cube	0.0
Pack Type	Color Box
Web Length	47.74
Web Width	1.42

COMPLIANCE

CA Regulations	Exempt - Base Not Regulated
CA Status	Lawful for sale in California
FCC Compliant	True
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cETLus
CA Compliance Text	Lawful for sale
DLC Approved	False
Title 20	Exempt
T24 Compliant	False