

Project Name

Location

Prepared By



SATCO S29854

9.5W/LED/CFL/3CCT/DUAL/4P

Notes

(www) 01-13-2023 01:25:55

General

Status	Active
Watts	9.5W
Fluorescent Equivalent	18W/26W/32W
Volts	120V-277V
Ballast Type	Type A/B
Shape	PL
Base	G24q (4-Pin)
ANSI Base	G24q
Finish	Frost
CCT (Kelvin)	3000K/3500K/4000K
Temperature	Warm to Cool White
CRI	80
Lumens	1100L/1150L/1200L
Beam Spread	360
Dimmable	Yes-Dimmable
Hours Rated	50000
Operating Position	Universal
Technology	LED

Electrical

Ballasting Requirements	Ballast required (Type A) or Ballast Bypass (Type B)
Operating Frequency	50/60Hz
Dimming Type	Triac
Dimming Note	Only in Type A mode; Check Ballast MFG for Dimmer Compatibility
Power Factor	0.9
THD	<20%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical

MOL	6.9
MOD	1.4
Weight (lb.)	0.2

Additional Information

Rated For Enclosed Fixture	Yes
Warranty	5 Year Limited - 10 hr per day

Compliance

Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Damp
NSF Approved	Yes
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes