


Sunlite 05279 LED Emergency Exit Sign Red, Dual Light with 90-Minute Battery Power Back-Up, 350 Degree Adjustable Head Lamps, 200 Lumens, 120-277V, Ceiling or Wall Mount, Long Lasting, Fire Safety

DESCRIPTION:

The Sunlite LED Emergency Exit Sign is a slim, low-profile Exit Sign with standard bright Red LED letters. If you are looking for an exit sign lighting solution that does not take over your decor, this sign is perfect for you! This exit sign operates on 120-277 volts, which is great for large complexes to small retail shops. This sign meets NFPA and OSHA requirements and is damp located which is great for restaurants, bars, and office environments. With its universal mounting, it can easily be mounted to a ceiling or wall.

FEATURES:

- SLIM & DURABLE The slim exit sign is made with highly durable plastic that is built to last. With its thermoplastic casing, it can operate with voltage ratings of 120V-277V, making it perfect for commercial buildings, residential complexes, and retail shops. Due to the slim design, this commercial exit sign is great for positioning in office buildings, warehouses, doorways, and aisles without taking over your décor.
- BRIGHT LED'S With its ultra-bright RED EXIT LED's, the exit sign can be seen from 200 meters away! (200 Lumens). The LEDs are bright enough to meet the standards of the NFPA and OSHA Exit Sign Requirements. Even with their high-intensity LEDs, they consume very little energy; 2.4 watts to be exact!
- BACK-UP BATTERY Installed with a built-in 3.6V/1000mAH Ni-CD battery. This backup battery provides 90-minutes of reserved power for outages. The adjustable LED lamps immediately go on when the power goes off. The battery automatically recharges within 24 hours after outages, so no replacement battery is necessary.
- EASY MOUNTING The Emergency Exit Sign can easily be mounted. With its universal mounting, this can easily become a single or double-sided ceiling exit sign. It could be mounted to a wall or flush mounted because the arrow plate snaps right out! (mounting hardware included)







SPECIFICATIONS:

General Characteristics

Material Lens Material

Finish

Lens Finish
Bulb Type
Application

Electrical Characteristics

 Watts
 2.4

 Volts
 120-277

Light Characteristics

Lumens Brightness 200

Fixture Characteristics

Number of Lights

Mounting

Fixture Technology

Use Location

White

2 Surface

Indoor

Thermoplastic White Housing

Plastic Frosted

Integrated LED Commercial

Integrated LED

Ite

Product Dimensions

Item Dimension (in)
Package Dimension (in)
Package Weight (lb)

Product Data

Case Unit Rate Item UPC

(W) 6.03 (H) 13.7 (D) 1.71 (W) 16.8 (H) 7.73 (D) 2.45 1.6

653703052793