

ST Series

Sunlite 17 Watt T8 High Performance Straight Tube, Medium Bi-Pin Base, Cool White

T8 High Performance Straight Tube

DESCRIPTION:

Sunlite fluorescent lamps are very popular for use in office and other lighting applications. The characteristics of fluorescent lamps vary from type of lamp. Fluorescents lamps are used so widely due to their low operating costs and because they are efficient, last for years, and are high quality and rapid starting. Fluorescent lamps can cost significantly less to operate over their lifetime than incandescent lamps. Life ratings for fluorescent lamps range from 6,000 to 36,000 hours based on the industry standard of 3 burning hours per start. Also, rapid start and instant start lamps typically start within 1 second of being turned on. The High Perfomance and High Output versions also give you and even better efficacy and energy efficiency. Look for a higher CRI for improved light quality. Sunlite 30125-SU F17T8/SP841 4100K Color Temperature T8 Hight Performance Straight Tube Fluorescent 17 Watt lamp features a Medium Bi Pin base, provides a light output of 1450 lumens at a Color Rendering Index (CRI) of 83 and can last an average of 20000 hours.



- 17-Watt
- 4100K Color Temperature
- 20,000 hour average lamp life

•







SPECIFICATIONS:

General Characteristics

Bulb Shape Average Rated Hours Base

Average Life Span Years

Electrical Characteristics

Watts

Light Characteristics

Lumens Brightness
Color Rendering Index CRI
Emitted Color

Color Temperature Kelvin

Mercury Content

Additional Features

Rohs Compliant

T8 20000

Medium 2-Pin (G13)

18

17

1450 83

Cool White 4100K

~4mg

Yes

Product Dimensions

Size
MOL (in)
Diameter (in)
Item Dimension (in)
Item Weight (lb)
Package Dimension (in)

Package Weight (lb)

Product Data

Case Unit Rate Pack Size Item UPC 30 1

2 Foot

24.00 1"

0.180

0.200

653703301259

(W) 1 (H) 1 (D) 23.1

(W) 1.05 (H) 1.05 (D) 23.8





VARIATIONS:



Item Number	Description	Watts	Lumens	CRI	Kelvin Color	Hours	Pack
30125-SU	F17T8/SP841	17	1450	83	4100K CW	20000	1
30105-SU	F17T8/SP830	17	1400	83	3000K WW	20000	1
30115-SU	F17T8/SP835	17	1450	83	3500K NW	20000	1
30126-SU	F17T8/SP850	17	1400	83	5000K SOFTWHITE	20000	1
30128-SU	F17T8/SP865	17	1400	83	6500K DL	20000	1