

ST Series**Sunlite F25T8/SP865/30PK 25 Watt T8
High Performance Straight Tube Medium
Bi-Pin (G13) Base, 6500K Daylight, 30
Pack**

T8 High Performance Straight Tube

DESCRIPTION:

Sunlite fluorescent 25 watt 6500k daylight T8 high performance straight tube features a medium bi-pin g13 base, provides a light output of 2300 lumens at a color rendering index (cri) of 83 and can last an average of, 20000 hours. These lamp utilize a single and double coat phosphor system.Â series lamps have an increased cri due to the use ofÂ tri-phosphors (rare earth phosphors). tri-phosphors also increase the lumens/watt output ofÂ the lamp.Â These series lamps offer superior quality ofÂ lighting, increased energy efficiencies, and extend life.

FEATURES:

- 25 Watt, Case of 30 Lamp
- T8 Light Bulb, Produces a spectacular Daylight Light at 6500K
- Simply remove and replace current bulbs
- Works with linear fluorescent rapid & instant start fixtures
- Ideal solution for commercial, industrial, sign, and display applications



SPECIFICATIONS:

General Characteristics

Bulb Shape	T8
Average Rated Hours	20000
Base	Medium 2-Pin (G13)
Average Life Span Years	18

Electrical Characteristics

Watts	25
-------	----

Light Characteristics

Lumens Brightness	2300
Color Rendering Index CRI	83
Emitted Color	Daylight
Color Temperature Kelvin	6500K

Product Dimensions

Size	3 Foot
MOL (in)	36.00
Diameter (in)	1.02"
Item Dimension (in)	(W) 1.02 (H) 36 (D) 1.02
Package Dimension (in)	(W) 1.05 (H) 1.05 (D) 35.75
Package Weight (lb)	0.290

Product Data

Case Unit Rate	30
Pack Size	1
Item UPC	653703301594

VARIATIONS:



Item Number	Description	Watts	Lumens	CRI	Kelvin Color	Hours	Pack
30159-SU	F25T8/SP865	25	2300	83	6500K DL	20000	1
30135-SU	F25T8/SP830	25	2300	83	3000K WW	20000	1
30145-SU	F25T8/SP835	25	2300	83	3500K NW	20000	1
30155-SU	F25T8/SP841	25	2300	83	4100K CW	20000	1
30158-SU	F25T8/SP850	25	2300	83	5000K SOFTWHITE	20000	1