

ST Series**Sunlite 28 Watt T8 High Performance
Straight Tube, Medium Bi-Pin Base,
Super White**

T8 High Performance Straight Tube

DESCRIPTION:

Sunlite fluorescent lamps are very popular for use in office and other lighting applications. The characteristics of fluorescent lamps vary type of lamp. Fluorescents lamps are used so widely due to their low operating costs and because they are efficient, last for years, and are high quality and rapid starting. Fluorescent lamps can cost significantly less to operate over their lifetime than incandescent lamps. Life ratings for fluorescent lamps range from 6,000 to 36,000 hours based on the industry standard of 3 burning hours per start. Also, rapid start and instant start lamps typically start within 1 second of being turned on. The High Performance and High Output versions also give you and even better efficacy and energy efficiency. Look for a higher CRI for improved light quality. Sunlite 30178-SU F28T8/SP850 5000K Color Temperature T8 Hight Performance Straight Tube Fluorescent 28 Watt lamp features a Medium Bi Pin base, provides a light output of 2400 lumens at a Color Rendering Index (CRI) of 83 and can last an average of 20000 hours.

FEATURES:

- 28-Watt
- 5000K Color Temperature
- 20,000 hour average lamp life
-
-



SPECIFICATIONS:

General Characteristics

Bulb Shape	T8
Average Rated Hours	20000
Base	Medium 2-Pin (G13)
Average Life Span Years	18

Electrical Characteristics

Watts	28
-------	----

Light Characteristics

Lumens Brightness	2400
Initial Lumens	2800
Mean Lumens	2660
Color Rendering Index CRI	83
Emitted Color	Super White
Color Temperature Kelvin	5000K

Product Dimensions

Size	4 Foot
MOL (in)	48.00
Diameter (in)	1"
Item Dimension (in)	(W) 1 (H) 1 (D) 48
Package Dimension (in)	(W) 1.05 (H) 1.05 (D) 47.75
Package Weight (lb)	0.320

Product Data

Case Unit Rate	30
Pack Size	1
Item UPC	653703301785

VARIATIONS:



Item Number	Description	Watts	Lumens	CRI	Kelvin Color	Hours	Pack
30178-SU	F28T8/SP850	28	2400	83	5000K SW	20000	1
30166-SU	F28T8/SP830	28	2400	83	3000K WW	20000	1
30177-SU	F28T8/SP841	28	2400	83	4100K CW	20000	1