

ST Series**Sunlite 32 Watt T8 High Performance
Straight Tube, Medium Bi-Pin Base, Cool
White**

T8 High Performance Straight Tube

DESCRIPTION:

Sunlite fluorescent lamps are very popular for use in office and other lighting applications. The characteristics of fluorescent lamps vary type of lamp. Fluorescent lamps are used so widely due to their low operating costs and because they are efficient, last for years, and are high quality and rapid starting. Fluorescent lamps can cost significantly less to operate over their lifetime than incandescent lamps. Life ratings for fluorescent lamps range from 6,000 to 36,000 hours based on the industry standard of 3 burning hours per start. Also, rapid start and instant start lamps typically start within 1 second of being turned on. The High Performance and High Output versions also give you and even better efficacy and energy efficiency. Look for a higher CRI for improved light quality. Sunlite 30195-SU F32T8/SP841 4100K Color Temperature T8 High Performance Straight Tube Fluorescent 32 Watt lamp features a Medium Bi Pin base, provides a light output of 3050 lumens at a Color Rendering Index (CRI) of 83 and can last an average of 20000 hours.

FEATURES:

- 32-Watt
- 4100K Color Temperature
- 20,000 hour average lamp life
-
-



SPECIFICATIONS:

General Characteristics

Bulb Shape	T8
Average Rated Hours	20000
Base	Medium 2-Pin (G13)
Average Life Span Years	18

Electrical Characteristics

Watts	32
--------------	----

Light Characteristics

Lumens Brightness	3050
Initial Lumens	3100
Mean Lumens	2925
Color Rendering Index CRI	83
Emitted Color	Cool White
Color Temperature Kelvin	4100K

Additional Features

Rohs Compliant	Yes
-----------------------	-----

Product Dimensions

Size	4 Foot
MOL (in)	48.00
Diameter (in)	1"
Item Dimension (in)	(W) 1 (H) 1 (D) 48
Item Weight (lb)	0.150
Package Dimension (in)	(W) 1.05 (H) 1.05 (D) 47.6
Package Weight (lb)	0.390
Cord Length	4 Foot

Product Data

Case Unit Rate	30
Pack Size	1
Item UPC	653703301952



VARIATIONS:



Item Number	Description	Watts	Lumens	CRI	Kelvin Color	Hours	Pack
30195-SU	F32T8/SP841	32	3050	83	4100K CW	20000	1
30165-SU	F32T8/SP830	32	3050	83	3000K WW	24000	1
30175-SU	F32T8/SP835	32	3050	83	3500K NW	24000	1
30199-SU	F32T8/SP850	32	3100	82	5000K SW	24000	1
30192-SU	F32T8/SP865	32	3050	83	6500K DL	20000	1