

**U-Shaped****Sunlite FB32/SP735/6 32-Watt FB32  
Linear Fluorescent Lamp Medium Bi Pin  
Base, 3500K**

T8 U-Bend Tube

**DESCRIPTION:**

*Sunlite fluorescent lamps are very popular for use in office and other lighting applications. The characteristics of fluorescent lamps vary type of lamp. Fluorescents lamps are used so widely due to their low operating costs and because they are efficient, last for years, and are high quality and rapid starting. Fluorescent lamps can cost significantly less to operate over their lifetime than incandescent lamps. Life ratings for fluorescent lamps range from 6,000 to 36,000 hours based on the industry standard of 3 burning hours per start. Also, rapid start and instant start lamps typically start within 1 second of being turned on. The High Performance and High Output versions also give you and even better efficacy and energy efficiency. Look for a higher CRI for improved light quality. Sunlite 30205-SU FB32/SP735/6 3500K Color Temperature T8 U-Bend Tube Fluorescent 32-Watt lamp features a Medium Bi Pin base, provides a light output of 2750 lumens at a Color Rendering Index (CRI) of 73 and can last an average of 20000 hours.*

**FEATURES:**

- T8 U-Bend Tube
- T8 U-Bend Tube
- T8 U-Bend Tube
- T8 U-Bend Tube
- T8 U-Bend Tube



SPECIFICATIONS:

General Characteristics

|                         |                       |
|-------------------------|-----------------------|
| Bulb Shape              | T8 U-Bend             |
| Average Rated Hours     | 20000                 |
| Base                    | Miniature Bi-Pin (G5) |
| Average Life Span Years | 18                    |

Electrical Characteristics

|       |    |
|-------|----|
| Watts | 32 |
|-------|----|

Light Characteristics

|                           |               |
|---------------------------|---------------|
| Lumens Brightness         | 2750          |
| Color Rendering Index CRI | 73            |
| Emitted Color             | Neutral White |
| Color Temperature Kelvin  | 3500K         |

Additional Features

|                |     |
|----------------|-----|
| Rohs Compliant | Yes |
|----------------|-----|

Product Dimensions

|                        |                          |
|------------------------|--------------------------|
| MOL (in)               | 22.5                     |
| Diameter (in)          | 1"                       |
| Item Dimension (in)    | (W) 6 (H) 1 (D) 22.5     |
| Package Dimension (in) | (W) 7.13 (H) 1.13 (D) 23 |
| Package Weight (lb)    | 0.850                    |

Product Data

|                |              |
|----------------|--------------|
| Case Unit Rate | 12           |
| Pack Size      | 1            |
| Item UPC       | 653703302058 |

