

MR Series**Sunlite 80440 LED PAR16 Short Neck Recessed Flood Light Bulb 6-Watt, (50W Halogen Replacement), 500 Lumens, Medium E26 Base, Dimmable, 90 CRI, ETL Listed, Title 20 Compliant, 1 Count, 5000K Daylight****High Efficiency****DESCRIPTION:**

From the moment you switch on our PAR16 short neck led bulbs, they will produce a flicker-free dimmable light. These bulbs are the perfect option for setting the tone in your living room, kitchen, or bedroom. With these PAR16 led bulbs, you will save up to 75% on your annual energy bill, instantly providing you with substantial savings. They have a lifespan of 25,000 hours and will reduce the hassle of replacing difficult-to-reach bulbs. Sunlite features the highest quality bulbs and fixtures designed to meet your home, office, or workplace needs. We are committed to providing our customers with outstanding service, expertise, and durable products. Our led PAR16 light bulbs are a worry-free choice, backed by our 2-year manufacturer warranty.

FEATURES:

- High Efficiency
- High Efficiency
- High Efficiency
- High Efficiency
- High Efficiency



SPECIFICATIONS:

General Characteristics

Bulb Shape	MR16
Average Rated Hours	25000
Base	Medium Screw (E26)
Average Life Span Years	23
Ingress Protection	IP20 (12.5 mm solids, Not protected from liquids)
Dimmable	Yes
Material	Plastic & Aluminum

Electrical Characteristics

Watts	6
Volts	120
Equivalent Wattage	50
LED Chip Manufacturer	SMD2835
Power Factor	0.9
Temperature	-4°F - 113°F

Light Characteristics

Lumens Brightness	500
Color Rendering Index CRI	90
Emitted Color	Super White
Color Temperature Kelvin	5000K
Beam Angle	35°
Beam Angle Description	Flood
Flicker	no

Additional Features

Safety Rating Mark	ETL - Damp Location
Title 20	Lawful for sale in California

Product Dimensions

MOL (in)	1.97
Diameter (in)	2.17
Item Dimension (in)	(W) 1.5 (H) 2.13 (D) 1.9
Package Dimension (in)	(W) 2 (H) 2.5 (D) 2
Package Weight (lb)	0.09

Product Data

Case Unit Rate	6
Pack Size	1
Item UPC	653703804408
Warranty Years	3
Package Type	Box

