

Sunlite 81289 12" LED Round Flush Mount Mini Panel Light Fixture, 22 Watts (=150W), Color Selectable 27K/30K/35K/40K/50K, 1500 Lumens, Dimmable, 90 CRI, ETL Listed, for Residential & Commercial Use

DESCRIPTION:

Mini Panel

Sunlite's 12" LED Round Flush Mount Mini Panel Fixture is an upgrade you'll need in every indoor application. It features a slim design with a polycarbonate housing material in white trim for wide range of applications. Additionally, it will be protected from contamination by small amounts of dust and other particles, thanks to its IP 54 rating. This fixture allows you to choose the color temperature prior to installation. Select 2700K or 3000K or 3500K or 4000K or 5000K, depending on your preference using a switch within the fixture. The lighting output can be dimmed when connected to an LED-compatible dimmer switch (10-100%) allowing you to adjust the brightness to suit the mood. It also features a wide 120-drgree beam angle. With a long 50,000-hour life span, these will provide years of reliable and maintenance-free service that only uses 22 watts of electricity. Estimated annual energy costs of \$2.65 (Based on 3 Hrs/Day at \$0.11/kWh). Installing these Energy Star Certified fixtures may qualify you for state or local energy rebates. ETL Listed for wet location installation. Mounting hardware and installation instructions included. Ideal for Kitchen, Office, Hallway, Bedroom and more. Fixture Dimension: 0.5" H x 12" D.

FEATURES:

- MODERN DESIGN It features a slim design with a polycarbonate housing material in white trim for wide range of applications. Additionally, it will be protected from contamination by small amounts of dust and other particles, thanks to its IP 54 rating.
- COLOR SELECTABLE This fixture allows you to choose the color temperature prior to installation. Select 2700K or 3000K or 3500K or 4000K or 5000K, depending on your preference using a switch within the fixture.
- DIMMABLE The lighting output can be dimmed when connected to an LED-compatible dimmer switch (10-100%) allowing you to adjust the brightness to suit the mood. It also features a wide 120-degree beam angle.
- ENERGY EFFICIENT With a long 50,000-hour life span,



and maintenance-free lectricity. Estimated ed on 3 Hrs/Day at Star Certified fixtures ergy rebates. cation installation. instructions included. edroom and more.

Fixture Dimension: 0.5" H x 12" D



SPECIFICATIONS:

General Characteristics

Average Rated Hours Finish Average Life Span Years

Average Life Span Years

Dimmable

Dimming Percentage

Material Lens Material Lens Finish

Application

Electrical Characteristics

Watts 22
Volts 120
Equivalent Wattage 100
Power Factor 0.9

Temperature -4°F - 104°F

50000

White

46

Yes

White

1500

CCT Selectable

27K/30K/35K/40K/50K

90

120°

10-100%

Aluminum & Plastic

Polycarbonate

Residential

Light Characteristics

Lumens Brightness
Color Rendering Index CRI

Emitted Color

Color Temperature Kelvin

Color remperature Keivii

Beam Angle

Fixture Characteristics

ShapeRoundMountingSurfaceFixture TechnologyLEDUse LocationIndoor

Additional Features

Safety Rating Mark ETL Listed - Wet Location

Mercury Free Yes

Product Dimensions

 Size
 12"

 MOL (in)
 0.5

 Diameter (in)
 11.75

Item Dimension (in)
Package Dimension (in)

Package Weight (lb)

11.75 (W) 12.5 (H) 12.31 (D) 1.22

(W) 12.88 (H) 13.5 (D) 13.25 1.89

Product Data

Case Unit Rate

Item UPC

Warranty Years

10

653703812892

5