

**Sunlite 81300 LED Coach Light Outdoor Fixture, 9 Watts (60W=), Multi-Volt, 600 Lumens, Color Selectable 30K/40K/50K, Dimmable, 80 CRI, ETL Listed, Black, for Porches, Garage & Entryways**  
Cage

**DESCRIPTION:**

Upgrade your outdoor fixtures to Sunlite's LED Coach Lights. This dimmable fixture uses only 9-watts of electricity while producing as much light as a 60-watt light bulb. When installing these fixtures, you can choose the color temperature between 3000K Warm White, 4000K Cool White or 5000K Daylight depending on your preferences. The lighting output can be changed when connected to an LED-compatible dimmer switch, allowing you to adapt the lighting to suit the mood. This fixture has a dimmable 600 lumen output. The integrated extended life LED technology offers 50,000 hours of maintenance-free service. ETL Listed for wet location installation. Ideal for Porches, Garage, Entryways and more. Mounting hardware and installation instructions included. Fixture Dimension: 13.75" H x 7.25" W x 9.5" D.

**FEATURES:**

- **DURABLE DESIGN** - Your home will always be bright and inviting in any temperature thanks to this fixture's strong cast aluminum and steel body, which is made for any outdoor placement. Its textured glass creates interesting light patterns through lattice lantern-type shade. It can withstand solid particles larger than 1mm in size as well as low-velocity water sprays coming from all directions thanks to its IP44 rating.
- **COLOR SELECTABLE** - This dimmable fixture uses only 9-watts of electricity while producing as much light as a 60-watt light bulb. When installing these fixtures, you can choose the color temperature between 3000K Warm White, 4000K Cool White or 5000K Daylight depending on your preferences.
- **DIMMABLE** - The lighting output can be changed when connected to an LED-compatible dimmer switch, allowing you to adapt the lighting to suit the mood.
- **LONG LIFE LED** - This fixture has a dimmable 600 lumen output. The integrated extended life LED technology offers 50,000 hours of maintenance-free service.
- **ETL LISTED** - ETL Listed for wet location installation. Ideal for Porches, Garage, Entryways and more. Mounting hardware and installation instructions included. Fixture Dimension: 13.75" H x 7.25" W x 9.5" D.



## SPECIFICATIONS:

### General Characteristics

|                                |                  |
|--------------------------------|------------------|
| <b>Average Rated Hours</b>     | 50000            |
| <b>Finish</b>                  | Black            |
| <b>Average Life Span Years</b> | 46               |
| <b>Dimmable</b>                | Yes              |
| <b>Material</b>                | Aluminum & Steel |
| <b>Lens Material</b>           | Glass            |
| <b>Lens Finish</b>             | Water Grain      |
| <b>Application</b>             | Outdoor          |

### Product Dimensions

|                               |                              |
|-------------------------------|------------------------------|
| <b>Item Dimension (in)</b>    | (W) 7.25 (H) 13.75 (D) 9.5   |
| <b>Package Dimension (in)</b> | (W) 10.63 (H) 17.38 (D) 8.75 |
| <b>Package Weight (lb)</b>    | 5.1                          |

### Product Data

|                       |              |
|-----------------------|--------------|
| <b>Case Unit Rate</b> | 4            |
| <b>Item UPC</b>       | 653703813004 |
| <b>Warranty Years</b> | 5            |

### Electrical Characteristics

|                              |              |
|------------------------------|--------------|
| <b>Watts</b>                 | 9            |
| <b>Volts</b>                 | 120-277      |
| <b>Equivalent Wattage</b>    | 60           |
| <b>LED Chip Manufacturer</b> | COB          |
| <b>Power Factor</b>          | 0.9          |
| <b>Temperature</b>           | -4°F - 113°F |

### Light Characteristics

|                                  |                |
|----------------------------------|----------------|
| <b>Lumens Brightness</b>         | 600            |
| <b>Color Rendering Index CRI</b> | 80             |
| <b>Emitted Color</b>             | CCT Selectable |
| <b>Color Temperature Kelvin</b>  | 30K/40K/50K    |
| <b>Beam Angle</b>                | 120°           |
| <b>Flicker</b>                   | >30%           |

### Fixture Characteristics

|                           |          |
|---------------------------|----------|
| <b>Style</b>              | Carriage |
| <b>Number of Lights</b>   | 1        |
| <b>Mounting</b>           | Wall     |
| <b>Fixture Technology</b> | LED      |
| <b>Use Location</b>       | Outdoor  |

### Additional Features

|                                |                           |
|--------------------------------|---------------------------|
| <b>Safety Rating Mark</b>      | ETL Listed - Wet Location |
| <b>Safety Rated For Canada</b> | Yes                       |
| <b>Safety Rated For USA</b>    | Yes                       |
| <b>Mercury Free</b>            | Yes                       |