

Sunlite 5-Inch Round Mini Panel Motion Sensor Light Fixture, 12 Watts, 700 Lumens, Color Selectable 27K/30K/35K/40K/50K, 90 CRI, Dimmable, ETL Listed, Energy Star, Title-24 Compliant



DESCRIPTION:

Sunlite's 5-Inch Round Mini Panel Motion Sensor is a versatile lighting solution. These dimmable motion sensor fixtures put out a bright 700 lumens and allow you to choose the color temperature at the time of installation. Select 2700K, 3000K, 3500K, 4000K or even 5000K depending on your preference using a switch located on the back of the fixture. Made of polycarbonate and plastic, it fits most 4" ceiling cans. High color rendering at 90 CRI. Bi-level PIR sensor allows the fixture to dim after motion is no longer detected. This feature can be disabled by simply switching it off. This feature can be disabled by simply switching it off. With a long 50,000-hour life span, these will provide years of reliable and maintenance-free service that only uses 12 watts of electricity. Estimated annual energy costs of \$1.45 (Based on 3 Hrs/Day at \$0.11/kWh). Installing these Energy Star Certified fixtures may qualify you for state or local energy rebates. These are ETL Listed for safety and quality. Dimension 5.7" W x 0.90" H x 5.7" D.

FEATURES:

- **COLOR TEMPERATURE SELECTABLE** - These dimmable motion sensor fixture put out a bright 700 lumens and allow you to choose the color temperature at the time of installation. Select 2700K, 3000K, 3500K, 4000K or even 5000K depending on your preference using a switch located on the back of the fixture.
- **EASY TO INSTALL** – Made of polycarbonate and plastic, it fits most 4" ceiling cans. It can be mounted directly to junction boxes and retrofitted to recessed lighting cans with the medium base adapter included. Mounting hardware & installation instructions are included. Retrofit accessories included.
- **DIMMABLE & MOTION SENSOR** - It can be dimmed (10%-100%) when installed with an LED compatible dimmer. High color rendering at 90 CRI. Bi-level PIR sensor allows the fixture to dim after motion is no longer detected. This feature can be disabled by simply switching it off. Left switch is used to turn off sensor function. Middle Bi-Level switch is used at normal of 25% rated wattage output, 100% wattage output when the PIR sensor is detected and Right On/Off switch normal is use at 0% output and 100% output when the PIR sensor is detected. NOTE: Sensor and dimming can't work together. One functionality should be turned off/not to be used.
- **ENERGY EFFICIENT** - With a long 50,000-hour life span, these will provide years of reliable and maintenance-free service that only uses 12 watts of electricity. Estimated

SPECIFICATIONS:

General Characteristics

Bulb Shape	Round
Average Rated Hours	50000
Finish	White
Base	Medium Screw (E26)
Average Life Span Years	46
Dimmable	Yes
Dimming Percentage	10-100%
Material	Plastic
Lens Finish	White
Application	Residential

Electrical Characteristics

Watts	12
Volts	120
Equivalent Wattage	40
LED Chip Manufacturer	2835 SMD
Power Factor	0.9
Temperature	-4°F - 104°F

Light Characteristics

Lumens Brightness	700
Color Rendering Index CRI	90
Emitted Color	CCT Selectable
Color Temperature Kelvin	27K/30K/35K/40K/50K

Fixture Characteristics

Shape	Round
Mounting	Surface
Photo Control	Yes
Motion Sensor	Yes
Fixture Technology	LED
Use Location	Indoor

Additional Features

Safety Rating Mark	ETL - Damp Location
Safety Rated For USA	Yes
Energy Star	Yes
Energy Star Number	2382048

Product Dimensions

Size	5"
Diameter (in)	5.7
Item Dimension (in)	(W) 5.7 (H) 0.9 (D) 5.7
Item Weight (lb)	0.99
Package Dimension (in)	(W) 9.37 (H) 6.18 (D) 1.75
Package Weight (lb)	0.99

Product Data

Case Unit Rate	12
Item UPC	653703813257
Warranty Years	5