

R Series

Sunlite 82035-SU LED 90 CRI R20 Reflector Bulb, 7 Watts (50W Equivalent), 525 Lumens, Dimmable, Medium Base (E26), Wide 105° Beam Angle, Energy Star Certified, ETL Listed, 30K - Warm White 6 Pack

90CRI Series

DESCRIPTION:

Sunlite 24-Inch Linear Battery Backup LED Fixtures are an energy efficient lighting option for ceiling or wall mounting. Built-in battery will provide up to 90 minutes of light in the event of a power outage. These hard wired fixtures are simple to install on any junction box and include installation hardware. Durable steel and plastic construction. Output is a bright 3000 lumen while only using 25 watts of electricity. Low annual energy costs of \$3.01 (Based on 3 Hours/Day at \$0.11/kWh). With integrated LEDs and a long 50,000 hour life span these fixtures will provide years of reliable and maintenance-free service. And unlike fluorescent tubes they are instant on at full brightness and contain no harmful chemicals. UL Listed for damp location installation. DLC Listed for quality and design. These indoor fixtures are ideal for residential or commercial installations in stairwells, corridors, storage areas, basements, garages, or anywhere extra lighting is needed.

FEATURES:

- **UPGRADE TO LED** - Easily upgrade your old bulbs with energy efficient LED technology. These dimmable bulbs use only 7 watts of electricity but are equal to a 50 watt incandescent bulb. Yet unlike incandescent or halogen bulbs they remain cooler to the touch.
- **DIMMABLE** - Emits a dimmable and comfortable warm white light at 3000K. Ideal for recessed cans, track lighting and other indoor fixtures with a medium (E26) base. High Color Rendering Index (CRI) rating of 90 for more vivid and true colors. Wide 105° beam angle.
- **LONG LIFE BULBS** - With an average life of 25,000 hours these LED bulbs provide years of reliable service and save the cost and hassle of replacing hard to reach bulbs.
- **ENERGY STAR CERTIFIED** - Installing these Energy Star Certified bulbs may qualify you for state and local energy rebates. Provides 525 lumens of light instantly with no warm up time needed. Mercury-free so there is no harmful hazardous waste. Standard R20 form factor. Overall length is 3.93 inches, 2.48 inches in diameter.
- **ETL LISTED** - These bulbs are ETL Listed for safety and quality. Ideal for both residential and commercial applications.



SPECIFICATIONS:

General Characteristics

Bulb Shape	R20
Average Rated Hours	25000
Base	Medium Screw (E26)
Average Life Span Years	23
Ingress Protection	IP20 (12.5 mm solids, Not protected from liquids)
Dimmable	Yes
Material	Plastic

Electrical Characteristics

Watts	7
Volts	120
Equivalent Wattage	50
LED Chip Manufacturer	Bridgelux
Power Factor	0.9
Temperature	-20-45°

Light Characteristics

Lumens Brightness	525
Color Rendering Index CRI	90
Emitted Color	Warm White
Color Temperature Kelvin	3000K
Beam Angle	105°

Additional Features

Safety Rating Mark	ETL - Damp Location
Energy Star	Yes
Energy Star Number	2347049

Product Dimensions

MOL (in)	3.93
Diameter (in)	2.48
Item Dimension (in)	(W) 2.48 (H) 3.91 (D) 2.48
Item Weight (lb)	0.015
Package Dimension (in)	(W) 4.5 (H) 7.8 (D) 5.7
Package Weight (lb)	1.050

Product Data

Case Unit Rate	12
Pack Size	6
Item UPC	653703820354
Warranty Years	3
Package Type	Box

