

Sunlite 82084 5/6-Inch LED Retrofit Gimbal Recessed Downlight Fixture, 11 Watts, 1100 Lumens, Color Selectable 27K/30K/35K/40K/50K, 90 CRI, Medium E26 Base, Dimmable, ETL Listed, White

DESCRIPTION:

The simple design of these Sunlite LED 5-Inch or 6-Inch LED Gimbal Recessed Downlight Fixture will add an elegant touch to any decor. Its gimbal design allows for tilting the light head 30 degrees in either direction and rotating nearly 360 degrees making it suitable for sloped ceilings and directional lightings. This dimmable fixture uses only 11 watts of electricity but provides as much light as a 75-watt light bulb with an output of 1100 lumens of light. These fixtures allow you to choose the color temperature at the time of installation. Select 2700K Warm White, 3000K Warm White, 3500K Neutral White, 4000K Cool White or 5000K Daylight depending on your preference using a switch located on the back of the fixture. It can be dimmed (10%-100%) when installed with an LED compatible dimmer. High color rendering at 90 CRI. Dimmer List: Lutron MACL-153M, SCL-153P, DVCL-153P, CTCL-153PDH-WH, TGCL-153PH-WH, DVWCL-153PH-WH. Leviton: Cat.NO.6674, R50-IPL06-10M. Legrand: RHCL453PTC, DCL453PTCCCV6, HCL453PTCCCV6. Provides up to 50,000 hours energy efficient light that only uses 11 watts of electricity. No maintenance, long-life LED technology means you won't need to climb ladders to replace difficult to reach bulbs. Easy to install with a medium base adapter and for ting on either 5" or 6" lights. Ideal for Entryways, Bedrooms, Kitchen, Hallway, Bathroom & more. These Energy Star Certified fixtures have a low annual estimated energy installing these fixtures may qualify you for state or local energy rebate programs. Estimated annual energy costs of \$1.32 (Based on 3 Hrs/Day at \$0.11/kWh). ETL Listed for safety and quality. Fixture Dimension: 2.9" Height x 7.2" Diameter.



FEATURES:

- **GIMBAL DESIGN** – Its gimbal design allows for tilting the light head 30 degrees in either direction and rotating nearly 360 degrees making it suitable for sloped ceilings and directional lightings.
- **COLOR SELECTABLE** - This dimmable fixture uses only 11 watts of electricity but provides as much light as a 75-watt light bulb with an output of 1100 lumens of light. These



or temperature at the
arm White, 3000K
4000K Cool White or
preference using a
ature.
%-100%) when installed
gh color rendering at 90

CRI. Dimmer List: Lutron MACL-153M, SCL-153P, DVCL-153P, CTCL-153PDH-WH, TGCL-153PH-WH, DVWCL-153PH-WH. Leviton: Cat.NO.6674, R50-IPL06-10M. Legrand: RHCL453PTC, DCL453PTCCCV6, HCL453PTCCCV6.

SPECIFICATIONS:

General Characteristics

Average Rated Hours	50000
Finish	White
Base	Medium Base (E26)
Average Life Span Years	46
Dimmable	Yes
Dimming Type	Forward Phase (Triac or Incandescent)
Dimming Percentage	10-100%
Material	Metal
Lens Material	Polycarbonate
Lens Finish	Frosted
Application	Residential

Product Dimensions

Size	5"/6"
MOL (in)	2.9"
Diameter (in)	7.2"
Item Dimension (in)	(W) 7.62 (H) 7.62 (D) 3.62
Item Weight (lb)	6.2
Package Dimension (in)	(W) 11.25 (H) 8.15 (D) 15.5
Package Weight (lb)	6.2

Product Data

Case Unit Rate	6
Item UPC	653703820842
Warranty Years	5

Electrical Characteristics

Watts	11
Volts	120
Equivalent Wattage	75
LED Chip Manufacturer	SMD
Power Factor	0.9
Temperature	0

Light Characteristics

Lumens Brightness	1100
Color Rendering Index CRI	90
Emitted Color	CCT Selectable
Color Temperature Kelvin	27K/30K/35K/40K/50K
Beam Angle	95°
Flicker	30%

Fixture Characteristics

Style	Recessed Gimbal
Shape	Round
Number of Lights	1
Mounting	Recessed
Fixture Technology	LED
Use Location	Indoor

Additional Features

Safety Rating Mark	ETL Listed - Wet Location
Safety Rated For Canada	Yes
Safety Rated For USA	Yes
Energy Star	Yes
Energy Star Number	2388769
Title 20	Lawful for sale in California
Rohs Compliant	Yes
Mercury Free	Yes