

**Sunlite 85552 2' LED Linear Strip Light
Fixture, 20W, 2300 Lmns, Selectable CCT
3000K-5000K, Dimmable, 50,000 Hour
Life Span, 83 CRI, Surface Mount, Steel
Body, ETL & DLC Listed**

Contemporary

DESCRIPTION:

Sunlite LED 2-Foot Linear Strip Light Fixtures are an energy-efficient and maintenance-free lighting solution. These hardwired fixtures have built-in LEDs, so there are no bulbs to replace. When connected to an LED-compatible dimmer, you can adjust the light output to suit your needs. These multi-volt 120-277V fixtures are ideal for various commercial, industrial, and residential applications—steel body with an acrylic lens designed for indoor use. With a 50,000-hour life span, these fixtures will provide years of maintenance-free service. Each fixture uses only 20 Watts of electricity and has an adjustable color temperature. They are ETL Listed for damp location use and DLC Listed for efficiency and design. The lens is made of shatterproof acrylic, and unlike fluorescent tube fixtures, they contain no harmful chemicals



FEATURES:

- **LED TECHNOLOGY** - The Sunlite Double Tube Strip Light Fixture is an excellent addition to any atmosphere. It features a slim, robust steel frame and a shatter-resistant frosted lens. These commercial lamps have built-in LEDs, so there are no bulbs to replace, making these a maintenance-free solution. Also, their service life is five times that of the standard fluorescent strip lights
- **DIMMABLE** - Fixture can be dimmed when installed with an LED-compatible dimmer. Output is a bright 2300 lumens while only using 20 watts of electricity. Operates within 120-277V AC, 10%-100% dimming range, low voltage dimmers capability (0-10V), and has a high color rendering at 83 CRI. The long 50,000-hour life span is significant in energy savings over time
- **ADJUSTABLE COLOR TEMPERATURE** - This simplistic fixture has adjustable LED color-selectable technology (3000K, 4000K, 5000K). A switch inside the fixture allows you to choose the color temperature that's just right for your application. **PLEASE NOTE:** Select the desired color temperature before completely mounting the fixture. (Instructions included)
- **EASY INSTALLATION** - The LED strip light is easily installed on any junction box and could be mounted in two ways, surface, and suspension. Directly mount this LED Wraparound fixture to the ceiling for bright light in offices, garages, basements, warehouses, and storage areas. Refer to installation instructions for detailed steps; mounting hardware is included
- **ETL LISTED** - With a 50,000-hour life span, these fixtures will provide years of maintenance-free service. These fixtures are perfect for commercial, industrial, and

SPECIFICATIONS:

General Characteristics

Average Rated Hours	50000
Finish	White
Average Life Span Years	46
Dimmable	Yes
Dimming Type	0-10V Low Voltage
Material	Steel
Lens Material	Acrylic
Lens Finish	White
Application	Commercial

Electrical Characteristics

Watts	20
Volts	120-277
Equivalent Wattage	20
LED Chip Manufacturer	SMD2835
Power Factor	0.9
Temperature	-20 +55

Light Characteristics

Lumens Brightness	2300
Color Rendering Index CRI	83
Emitted Color	CCT Selectable
Color Temperature Kelvin	30K/40K/50K
Beam Angle	108°

Fixture Characteristics

Mounting	Surface
Fixture Technology	LED
Use Location	Indoor

Additional Features

Safety Rating Mark	ETL - Damp Location
Safety Rated For Canada	Yes
Safety Rated For USA	Yes
DLC	Yes
DLC Number	PDD445GE
DLC Classification	Standard
Mercury Free	Yes

Product Dimensions

Size	24"
Item Dimension (in)	(W) 3.78 (H) 2.37 (D) 24
Item Weight (lb)	3.04
Package Dimension (in)	(W) 3.78 (H) 2.37 (D) 48
Package Weight (lb)	3.04

Product Data

Case Unit Rate	6
Item UPC	653703855523
Warranty Years	5