

Sunlite 85555 2" Round Deep Anti-Glare Recessed Downlight, 8 Watt, 600 Lumens, 4000K Cool White, Dimmable, 90 CRI, ETL Listed, White, For Residential & Commercial Use

DESCRIPTION:

Add a classic touch to any home or business with Sunlite's 2" Round Deep Anti-Glare Recessed Downlight. The deep antiglare downlights are designed to provide a comfortable light environment that can distribute a uniform light. Color temperature is 4000K Cool White with a bright 600-lumen output. Made of robust die-cast aluminum alloy for optimal heat dissipation and built to last so that it can serve you a long time. Refer to installation instructions for detailed steps; mounting hardware is included. It can be dimmed (10%-100%) when installed with an LED compatible dimmer. High color rendering at 90 CRI. Dimmer List: Lutron CTCL-153P, DVCL-153P, S-600P, SLV-600P, CN-600P. Leviton: 6674, 6672. With a long 50,000-hour life span, these will provide years of reliable and maintenance-free service that only uses 8 watts of electricity. Estimated annual energy costs of \$0.96 (Based on 3 Hrs/Day at \$0.11/kWh). Benefit from significant energy savings over time. These are ETL Listed for safety and quality. Unlike fluorescent tubes they contain no harmful chemicals. Ideal for Living Rooms, Conference Room, Bedrooms, Kitchen, Porches & Closets.

FEATURES:

- DEEP ANTI-GLARE The deep anti-glare downlights are designed to provide a comfortable light environment that can distribute a uniform light. Color temperature is 4000K Cool White with a bright 600-lumen output.
- DURABLE Made of robust die-cast aluminum alloy for optimal heat dissipation and built to last so that it can serve you a long time. Refer to installation instructions for detailed steps; mounting hardware is included.
- DIMMABLE It can be dimmed (10%-100%) when installed with an LED compatible dimmer. High color rendering at 90 CRI. Dimmer List: Lutron CTCL-153P, DVCL-153P, S-600P, SLV-600P, CN-600P. Leviton: 6674, 6672.
- LONG LIFE SPAN With a long 50,000-hour life span, these will provide years of reliable and maintenance-free service that only uses 8 watts of electricity. Estimated annual energy costs of \$0.96 (Based on 3 Hrs/Day at \$0.11/kWh). Benefit from significant energy savings over



hese are ETL Listed for safety and quality. nt tubes they contain no harmful chemicals.
Rooms, Conference Room, Bedrooms, s & Closets.





SPECIFICATIONS:

General Characteristics

Average Rated Hours **Finish**

Average Life Span Years

Dimmable **Dimming Type**

Dimming Percentage

Material Lens Material

Lens Finish **Application**

Electrical Characteristics

8 Watts Volts 120 Equivalent Wattage 60 Power Factor 0.9

-4° - 104°F **Temperature**

50000

White

46

Yes

Forward Phase (Triac or

Incandescent)

Aluminum & Plastic

10-100%

PMMA

White

600

90

Cool White

4000K 36°

Indoor

Residential

Light Characteristics

Lumens Brightness Color Rendering Index CRI

Emitted Color Color Temperature Kelvin

Beam Angle

Fixture Characteristics

Regressed Downlight Style Shape Round Mounting Recessed IC Rating Yes Fixture Technology **LED**

Additional Features

Use Location

Safety Rating Mark ETL - Damp Location

Mercury Free Yes **Product Dimensions**

2" Size MOL (in) Diameter (in)

Item Dimension (in) Item Weight (Ib)

Package Dimension (in) Package Weight (lb)

Product Data

Case Unit Rate Pack Size Item UPC

Warranty Years

2.64 3.15

(W) 6.25 (H) 3.19 (D) 4.94

10.55

(W) 10.75 (H) 10.62 (D) 13.25

10.55

12 1

653703855554

5