

DESCRIPTION:

Highlighting a dedication to quality and integrity, the Sunlite product line includes light bulbs of LED, linear fluorescent, compact fluorescent, incandescent, HID metal halide, halogen, decorative, and specialty lamps. In addition, the Sunlite line includes various indoor and outdoor commercial, Industrial, and residential fixtures. Electrical products include extension cords, socket adapters, wall plates, receptacles and switches, dimmers, timers, surge protectors, and much more.

FEATURES:

-
-
-
-
-



SPECIFICATIONS:

General Characteristics

Average Rated Hours	50000
Finish	White
Average Life Span Years	46
Dimmable	Yes
Dimming Type	0-10V Low Voltage
Dimming Percentage	10-100%
Material	Metal & Plastic
Lens Material	Plastic
Lens Finish	Frosted
Application	Commercial

Electrical Characteristics

Watts	25/30/40
Volts	120-277
LED Chip Manufacturer	Bridgelux
Power Factor	0.9
Temperature	-4°F - 122°F

Light Characteristics

Lumens Brightness	2750/3300/4400
Color Rendering Index CRI	80
Emitted Color	CCT Selectable
Color Temperature Kelvin	35K/40K/50K
Beam Angle	110°

Fixture Characteristics

Mounting	Recessed
IC Rating	Yes
Fixture Technology	LED
Use Location	Indoor

Additional Features

Safety Rating Mark	UL Listed - Damp Location
Safety Rated For Canada	Yes
Safety Rated For USA	Yes
DLC	Yes
DLC Number	S-AO1JH0
DLC Classification	Standard
Rohs Compliant	Yes
Mercury Free	Yes

Product Dimensions

Size	2X2
Item Dimension (in)	(W) 23.7 (H) 1.5 (D) 23.7

Product Data

Pack Size	4
Item UPC	10653703856107
Warranty Years	5

ACCESSORIES:

Catalog # 85144-SU
LFX/FLAT/2X2

Catalog # 85148-SU
LFX/FLAT/2X2

Catalog # 85129-SU
LFX/FLAT/1X4