

ST Series

Bypass Dual End

DESCRIPTION:

Highlighting a dedication to quality and integrity, the Sunlite product line includes light bulbs of LED, linear fluorescent, compact fluorescent, incandescent, HID metal halide, halogen, decorative, and specialty lamps. In addition, the Sunlite line includes various indoor and outdoor commercial, Industrial, and residential fixtures. Electrical products include extension cords, socket adapters, wall plates, receptacles and switches, dimmers, timers, surge protectors, and much more.

FEATURES:

- Bypass Dual End
- Bypass Dual End
- Bypass Dual End
- Bypass Dual End
- Bypass Dual End



SPECIFICATIONS:

General Characteristics

Bulb Shape	T5
Average Rated Hours	50000
Finish	White
Base	Miniature Bi-Pin (G5)
Average Life Span Years	46
Dimmable	No
Material	Glass+PET

Electrical Characteristics

Watts	16
Volts	120-277
Equivalent Wattage	F39T5
LED Chip Manufacturer	2835
Power Factor	0.9
Temperature	-20° to 45°

Light Characteristics

Lumens Brightness	1800
Color Rendering Index CRI	80
Emitted Color	Warm White
Color Temperature Kelvin	3000K
Beam Angle	160°
Flicker	70%-75%

Additional Features

Safety Rating Mark	UL Listed
Safety Rated For Canada	Yes
Safety Rated For USA	Yes

Product Dimensions

Size	3 Foot
MOL (in)	35.7
Diameter (in)	0.82
Item Dimension (in)	(W) 0.73 (H) 0.73 (D) 33.35
Item Weight (lb)	0.280
Package Dimension (in)	(W) 0.73 (H) 0.73 (D) 33.36
Package Weight (lb)	0.280

Product Data

Case Unit Rate	10
Pack Size	1
Item UPC	653703879901
Warranty Years	5
Package Type	Sleeve

