

## Sunlite 88129 LED Outdoor Canopy Light Fixture, Power Selectable 30W/40W/60W, 3900/5200/7800 Lumens, Color Selectable 30K/40K/50K, 80 CRI, ETL Listed, Bronze, For Commercial & Industrial Use

### Canopy

#### **DESCRIPTION:**

Upgrade your canopy lights and reduce energy costs with LED fixtures from Sunlite. Each unit contains 240 energy efficient LEDs that are instant on with no warm up time at a bright 7800 lumens max. Dimmable fixture puts out a bright 7800 lumen max and allows you to choose the color temperature at the time of installation. Selectable 30K/40K/50K. Take control of the light emitted with its selectable wattage of 30W/40W/60W. Wide 105-degree beam for optimal coverage and long 50,000-hour lifespan. Designed for outdoor use with weatherproof aluminum base and polycarbonate lens. With no bulbs to replace, this vandal proof fixture is a maintenance-free lighting solution for commercial and industrial applications. These commercial grade fixtures are made from weatherproof aluminum with a bronze finish and a polycarbonate lens. Wide 105-degree beam angle. These vandal proof fixtures are ideal for gas station canopies, parking structures, underpasses, security lighting, and more.

#### **FEATURES:**

- **UPGRADE TO LED** - Sunlite LED Canopy Light Fixtures provide ample illumination and high visibility while saving energy compared to halogen, metal halide, or high-pressure sodium lights. They are instant on at full brightness with no warm-up time. Integrated LEDs mean no bulbs to replace.
- **LONG LIFE SPAN** - A long, 50,000-hour lifespan means years of reliable and maintenance-free service with no bulbs to replace. Benefit from significant energy savings over time.
- **MULTIPLE OUTDOOR USES** - These commercial grade fixtures are made from weatherproof aluminum with a bronze finish and a polycarbonate lens. Wide 105-degree beam angle. These vandal proof fixtures are ideal for gas station canopies, parking structures, underpasses, security lighting, and more.
- **COLOR TEMPERATURE & POWER SELECTABLE** - This dimmable fixture puts out a bright 3900/5200/7800 lumen and allows you to choose the color temperature at the time of installation. Selectable 30K/40K/50K. Take control of the light emitted with its selectable wattage of 30W/40W/60W.
- **ETL LISTED** - These fixtures are ETL Listed for wet location installation and not rated for enclosed fixtures. These commercial-grade fixtures are made from weatherproof aluminum with a bronze finish and a polycarbonate lens. Wide 105-degree beam angle. They operate on 120–277-volt service. Includes 12" grounded cord.



## SPECIFICATIONS:

### General Characteristics

Average Rated Hours	50000
Finish	Bronze
Average Life Span Years	46
Dimmable	Yes
Dimming Type	0-10V Low Voltage
Dimming Percentage	0-100%
Material	Aluminum
Lens	Clear
Lens Material	Polycarbonate
Lens Finish	Blow molding
Application	Commercial

### Electrical Characteristics

Watts	30/40/60
Volts	120-277
LED Chip Manufacturer	2835
Power Factor	0.9
Temperature	-40°F - 104°F

### Light Characteristics

Lumens Brightness	3900/5200/7800
Color Rendering Index CRI	80
Emitted Color	CCT Selectable
Color Temperature Kelvin	30K/40K/50K
Beam Angle	105°

### Fixture Characteristics

Shape	Square
Mounting	Surface
Fixture Technology	LED
Use Location	Outdoor

### Additional Features

Safety Rating Mark	ETL Listed
DLC	Yes
DLC Classification	Premium

### Product Dimensions

MOL (in)	3.40"
Diameter (in)	10.23"
Item Dimension (in)	(W) 10.23 (H) 10.23 (D) 10.23
Package Dimension (in)	(W) 11.44 (H) 4.87 (D) 11.44
Package Weight (lb)	6.08
Canopy Width (in)	3.40"
Cord Length	12"

### Product Data

Case Unit Rate	6
Item UPC	653703881294
Warranty Years	5