

ST Series

Sunlite LED T5 Plug and Play 25W Light Bulb (G5) Base, Super White

Plug and Play

DESCRIPTION:

Sunlite Lighting's LED T5 lamps deliver a comfortable but vivid and flicker-free ray of light to any setting. Consuming only 25 watts of energy to produce a stunning 5000K Super White light in addition to offering significant energy savings when compared to competing bulbs. Ideal for various settings while not utilizing any hazardous chemicals, such as Mercury. Featuring a (G5) base, they are designed to fit in a variety of applications. With an average lamp life of 50000 hours, Sunlite Lighting's T5 bulbs do more than just illuminate a room; these bulbs add a layer of life to any and all dÃ©cor. Warning Before installing, be sure to confirm this T8 Plug & Play lamp is compatible with your ballast. The Ballast Compatibility List can be found on www.sunlite.com under the specific Item Number. Make sure the lighting fixture is wired correctly per the ballast or lamp instructions. Never install or remove the T8 lamp with the lighting fixture energized, or arcing at the pins may occur. Sunshine Lighting assumes no liability for incidental or consequential damages resulting from the misuse of this product.

FEATURES:

- Produces An Efficient 5000K Super White Beam Of Light For All Your Ceiling Fixtures And More
- On Average, These Light Bulbs Last An Astonishing 50000 Hours
- First-Class Plug And Play Tube Lighting That Consumes 25 Watts Of Energy; Replaces Standard Linear Fluorescent Light Bulbs
- 4 Foot Tubular LED Plug And Play Bulb Perfect For Your Bathroom, Hallway, And/Or Office's Compatible Ceiling Light Fixtures
- High-Quality, UL Listed, Modern Replacement LED Light Bulbs Sold At A Highly Competitive Price



SPECIFICATIONS:

General Characteristics

Bulb Shape	T5
Average Rated Hours	50000
Finish	White
Base	Miniature Bi-Pin (G5)
Average Life Span Years	46
Dimmable	No
Material	Glass

Electrical Characteristics

Watts	25
Equivalent Wattage	F54T5/HO
LED Chip Manufacturer	2835
Power Factor	0.9
Temperature	-20° to 45°
Ballast Factor	High Output (HO) Required

Light Characteristics

Lumens Brightness	3200
Color Rendering Index CRI	82
Emitted Color	Super White
Color Temperature Kelvin	5000K
Beam Angle	180°

Additional Features

Safety Rating Mark	UL Listed - Damp Location
UL Rated Enclosed Fixtures	Yes
DLC	Yes
DLC Number	PL3OND2LNN12
DLC Classification	Standard

Product Dimensions

Size	4 Foot
MOL (in)	45.8
Diameter (in)	0.64
Item Dimension (in)	(W) 0.62 (H) 45.8 (D) 0.62
Package Dimension (in)	(W) 45.5 (H) 0.62 (D) 0.62
Package Weight (lb)	0.300

Product Data

Case Unit Rate	10
Pack Size	1
Item UPC	653703882307
Warranty Years	5
Package Type	Sleeve

