

ST Series

Sunlite 88426 LED T5 Ballast Bypass Light Tube (Type B) 4 Foot, 25 Watt (F54T5 Fluorescent Replacement) 3500 Lm, Mini G5 Base, Dual End Connection UL Listed, Shatterproof, 6500K Daylight, 25 Pack

Bypass Dual End

DESCRIPTION:

Upgrade your T5 fluorescent bulbs with led energy efficient food safe ballast bypass bulbs. They are instant on at full brightness with no buzzing or flickering. With a life span of up to 50,000 hours you will be required to replace difficult to reach bulbs less often. You'll save maintenance costs and save energy at the same time. These T5 shatterproof bulbs can be used for both commercial and residential locations. They are UL Listed and unlike fluorescent tubes, they contain no harmful chemicals and do not require special handling or disposal.

FEATURES:

- **UPGRADE TO LED** - Replace your inefficient T5 fluorescent bulbs with energy saving LED bulbs from Sunlite. They are instant on at full brightness with no buzzing or flickering. Glass outer tubes prevent yellowing and bending over time. High Color Rendering Index (CRI) rating of 80
- **BALLAST BYPASS REQUIRED** - These bulbs are direct replacements for 4 foot G5 (mini) base T5 fluorescent tubes. You must bypass the ballast in all fixtures before installing these bulbs. Simple instructions can be found online or consult an electrician for more information
- **ENERGY EFFICIENT** - With a life span of up to 50,000 hours each bulb puts out a bright 3500 lumens of light with a 6500K daylight temperature while only using 25 watts of electricity. Annual energy costs are a low \$3.01 (Based on 3 hours/day at \$0.11/kWh)
- **UL LISTED** - These T5 bulbs are UL Listed and is tested to meet their rigorous safety standards for quality and efficiency. Unlike fluorescent tubes, led tubes contain no harmful chemicals and do not require special handling or disposal
- **FOOD & RESTAURANT SAFE** - This T5 bulb is covered with pet film which prevents shattered glass from dispersing. Unlike fluorescent tubes, led tubes contain no harmful chemicals and do not require special handling or disposal, making it the perfect option for restaurant and food applications



SPECIFICATIONS:

General Characteristics

Bulb Shape	T5
Average Rated Hours	50000
Finish	White
Base	Bi-Pin (G5)
Average Life Span Years	46
Dimmable	No

Electrical Characteristics

Watts	25
Equivalent Wattage	F28T5

Light Characteristics

Lumens Brightness	3500
Color Rendering Index CRI	80
Emitted Color	Daylight
Color Temperature Kelvin	6500K

Additional Features

Safety Rating Mark	UL Classified - Damp Location
---------------------------	-------------------------------

Product Dimensions

MOL (in)	45.8
Item Dimension (in)	(W) 0.82 (H) 0.82 (D) 45.4
Package Dimension (in)	(W) 4.75 (H) 4.5 (D) 47
Package Weight (lb)	11.94

Product Data

Case Unit Rate	25
Pack Size	1
Item UPC	653703884264
Warranty Years	5
Package Type	Sleeve

