

ST Series

Bypass Dual End

DESCRIPTION:

Highlighting a dedication to quality and integrity, the Sunlite product line includes light bulbs of LED, linear fluorescent, compact fluorescent, incandescent, HID metal halide, halogen, decorative, and specialty lamps. In addition, the Sunlite line includes various indoor and outdoor commercial, Industrial, and residential fixtures. Electrical products include extension cords, socket adapters, wall plates, receptacles and switches, dimmers, timers, surge protectors, and much more.

FEATURES:

-
-
-
-
-



SPECIFICATIONS:

General Characteristics

Bulb Shape	T8
Average Rated Hours	50000
Finish	White
Base	Medium 2-Pin (G13)
Average Life Span Years	46
Dimmable	No
Material	Glass

Electrical Characteristics

Watts	12
Volts	120-277
Equivalent Wattage	F21T5, F25T8, F30T12
Power Factor	0.9
Temperature	-20° to 45°

Light Characteristics

Lumens Brightness	1450
Color Rendering Index CRI	82
Emitted Color	Daylight
Color Temperature Kelvin	6500K

Additional Features

Safety Rating Mark	UL Listed - Damp Location
UL Rated Enclosed Fixtures	Yes
Safety Rated For Canada	Yes
Safety Rated For USA	Yes

Product Dimensions

Size	3 Foot
MOL (in)	35.7
Diameter (in)	0.98
Package Dimension (in)	(W) 36 (H) 1 (D) 1.01
Package Weight (lb)	0.350

Product Data

Case Unit Rate	10
Pack Size	1
Item UPC	653703884486
Warranty Years	5
Package Type	Sleeve

