

## ST Series

### Bypass Dual End

#### **DESCRIPTION:**

*Highlighting a dedication to quality and integrity, the Sunlite product line includes light bulbs of LED, linear fluorescent, compact fluorescent, incandescent, HID metal halide, halogen, decorative, and specialty lamps. In addition, the Sunlite line includes various indoor and outdoor commercial, Industrial, and residential fixtures. Electrical products include extension cords, socket adapters, wall plates, receptacles and switches, dimmers, timers, surge protectors, and much more.*

#### **FEATURES:**

- 
- 
- 
- 
- 



## SPECIFICATIONS:

### General Characteristics

|                                |                       |
|--------------------------------|-----------------------|
| <b>Bulb Shape</b>              | T5                    |
| <b>Average Rated Hours</b>     | 50000                 |
| <b>Finish</b>                  | White                 |
| <b>Base</b>                    | Miniature Bi-Pin (G5) |
| <b>Average Life Span Years</b> | 46                    |
| <b>Dimmable</b>                | No                    |
| <b>Material</b>                | Glass                 |

### Electrical Characteristics

|                           |             |
|---------------------------|-------------|
| <b>Watts</b>              | 13          |
| <b>Volts</b>              | 120-277     |
| <b>Equivalent Wattage</b> | F28T5       |
| <b>Power Factor</b>       | 0.9         |
| <b>Temperature</b>        | -20° to 45° |

### Light Characteristics

|                                  |            |
|----------------------------------|------------|
| <b>Lumens Brightness</b>         | 1650       |
| <b>Color Rendering Index CRI</b> | 80         |
| <b>Emitted Color</b>             | Cool White |
| <b>Color Temperature Kelvin</b>  | 4000K      |
| <b>Beam Angle</b>                | 240°       |

### Additional Features

|                                   |                               |
|-----------------------------------|-------------------------------|
| <b>Safety Rating Mark</b>         | UL Classified - Damp Location |
| <b>UL Rated Enclosed Fixtures</b> | Yes                           |
| <b>Safety Rated For Canada</b>    | Yes                           |
| <b>Safety Rated For USA</b>       | Yes                           |
| <b>DLC</b>                        | Yes                           |
| <b>DLC Number</b>                 | PLK63MMWBBSF                  |
| <b>DLC Classification</b>         | Standard                      |

### Product Dimensions

|                               |                             |
|-------------------------------|-----------------------------|
| <b>Size</b>                   | 4 Foot                      |
| <b>MOL (in)</b>               | 45.8                        |
| <b>Diameter (in)</b>          | 0.82                        |
| <b>Item Dimension (in)</b>    | (W) 0.82 (H) 0.82 (D) 45.45 |
| <b>Item Weight (lb)</b>       | 0.440                       |
| <b>Package Dimension (in)</b> | (W) 0.87 (H) 0.87 (D) 45.45 |
| <b>Package Weight (lb)</b>    | 0.440                       |

### Product Data

|                       |              |
|-----------------------|--------------|
| <b>Case Unit Rate</b> | 25           |
| <b>Pack Size</b>      | 1            |
| <b>Item UPC</b>       | 653703884875 |
| <b>Warranty Years</b> | 5            |
| <b>Package Type</b>   | Sleeve       |

