

Sunlite 89129 LED Selectable 5-6" Square Retrofit Light Fixture, 14W, 1100 Lmns Recessed Downlight Ceiling Mount, 27K/30K/35K/40K/50K Selectable CCT Dimmable, 90 CRI, ETL Listed, 1 Count

DESCRIPTION:

Sunlite selectable 5-6" retrofit surface mount ceiling light fixture is designed for indoor use. The slim and simplistic design blends perfectly into any modern setting where downlights are required. These easy to install, dimmable fixtures have built-in energy-efficient LED technology, so there are no bulbs to replace. Durable steel body and opaque white lens. With a life span of up to 50,000 hours, it is an ideal, no maintenance solution for home and business installations

FEATURES:

- **SLIM AND STYLISH** - Upgrade your 5-6" ceiling cans to LED. This square LED recessed downlight fixture is a stylish addition to any décor. It features a E26 medium base and metal body with white trim and a shatter-resistant frosted lens
- **COLOR SELECTABLE** - This selectable fixture features innovative technology that allows you to choose the color temperature with a switch at the time of installation. Select 2700K, 3000K 3500K, 4000K, and 5000K depending on your preference
- **DIMMABLE** – The fixture can be dimmed when installed with an LED compatible dimmer. Output is a bright 1100 lumens while only using 14 watts of electricity which is 75W equivalent. High color rendering at 90 CRI
- **LONG LIFE, NO MAINTENANCE** - With a life span of up to 50,000 hours and a built-in LED, this fixture is an ideal, no maintenance lighting solution
- **ETL LISTED** - ETL Listed for wet location installation and Energy Star certified. Each fixture includes installation hardware and instructions. Estimated annual energy costs of \$1.69 based on 3 hours/day use



SPECIFICATIONS:

General Characteristics

Bulb Shape	Integrated LED
Average Rated Hours	50000
Finish	White
Base	Medium Screw (E26)
Average Life Span Years	46
Dimmable	Yes
Dimming Type	Forward Phase (Triac or Incandescent)
Dimming Percentage	10-100%
Material	Aluminum
Lens Finish	White
Bulb Type	Integrated
Application	Residential

Electrical Characteristics

Watts	14
Volts	120
LED Chip Manufacturer	bridgelux 2835
Power Factor	0.9
Temperature	-20~40

Light Characteristics

Lumens Brightness	1100
Color Rendering Index CRI	90
Emitted Color	CCT Selectable
Color Temperature Kelvin	27K/30K/35K/40K/50K
Beam Angle	110°
Flicker	30%

Fixture Characteristics

Shape	Square
Number of Lights	1
Mounting	Recessed
Fixture Technology	LED
Use Location	Indoor

Additional Features

Safety Rating Mark	ETL Listed - Wet Location
Safety Rated For Canada	Yes
Safety Rated For USA	Yes
Energy Star	Yes
Energy Star Number	2386239
Mercury Free	Yes

Product Dimensions

Size	5"/6"
MOL (in)	3.57
Diameter (in)	7.33
Item Dimension (in)	(W) 6 (H) 1.06 (D) 6
Package Dimension (in)	(W) 8 (H) 3.38 (D) 7.75
Package Weight (lb)	1.21

Product Data

Case Unit Rate	12
Pack Size	1
Item UPC	653703891293
Warranty Years	5