

# LEDVANCE Luminaires

## MULTIPURPOSE UTILITY LIGHT

PERFORMANCE CLASS

### Application

The LEDVANCE Performance Class Multipurpose Utility Light is a new ultra slim retrofit lamp, focused on lighting efficiency and modern design. This luminaire offers energy savings up to 68% and high quality color reproduction. This luminaire was designed for residential, low bay applications including garages, workshops, and attics.

### Benefits and Features

- Ultra slim design for a modern look
- Clear bright light offers uniform, glare free illumination distribution
- Adjustable panels allow for customizable light
- Up to 120 LPW
- 5000K color temperature
- CRI >80
- Offered in 60, 80, and 100 watts
- Energy savings up to 68%

### Electrical

- 120VAC
- 1.5kV surge protection
- Power Factor >90%
- THD <20%
- 113° beam angle

### Rated Life

- 50,000 hours (L<sub>70</sub>)

### Warranty

- 5-year
- NLB Trusted Warranty Program

### Ambient Operating Range

- -22°F to +104°F (-30°C to +40°C)



### Wattage Comparison

Traditional Source	LED System Wattage	Energy Savings
120W CFL	60	50%
175W HPS	60	66%
150W CFL	80	47%
250W MH	80	68%
200W CFL	100	50%
250W MH	100	60%

### Certifications and Listings

- cULus
- RoHS
- FCC

### Installation

- Screw-based design intended to replace traditional technologies



Specification Data

Catalog #	Type
Project	
Comments	
Prepared by	

Ordering Guide


LED	XXX	GARAGE	8	50	MED
LED	Wattage	Lamp Type	CRI	Color Temperature	Base Type
LED Technology	60 = 60 Watts 80 = 80 Watts 100 = 100 Watts	GARAGE = Garage Light	8 = >80	50 = 5000K	MED = Medium Base

Ordering Information


Item Number	Ordering Abbreviation	Total Wattage (W)	Input Voltage (V)	Dimming	CRI	Color Temperature	Base	Total Fixture Lumens (lm)	LPW	DLC	SKU Quantity
41394	LED60GARAGE850MED	60	120V	No	>80	5000K	Medium	7200	120	Exempt	1EA
41395	LED80GARAGE850MED	80	120V	No	>80	5000K	Medium	9600	120	Exempt	1EA
41396	LED100GARAGE850MED	100	120V	No	>80	5000K	Medium	12,000	120	Exempt	1EA

Physical Information

Folded




Unfolded




Dimensions in inches (mm)

## Photometric Information


60W



80W




100W




## Illuminance Information


60W



80W



100W



## Additional Specifications

- Suitable for damp locations
- Suitable for use in enclosed luminaires
- IP44 Rating

LEDVANCE LLC

181 Ballardvale Street, Suite 203

Wilmington, MA 01887 USA

Phone 1-800-LIGHTBULB (1-800-544-4828)

www.ledvanceUS.com

SYLVANIA and LEDVANCE are registered trademarks.

All other trademarks are those of their respective owners.

Licensee of product trademark SYLVANIA in general lighting.


Specifications subject to change without notice.



/sylvania



/sylvania



LEDVANCE