

LEDVANCE LUMINAIRES

PERFORMANCE CLASS

OPTI-SELECT AREA LIGHT

OPTISELECT

LEDVANCE LUMINAIRE SPECIFICATION DATA

Catalog #	Comments
Project	
Type	
Prepared by	

PERFORMANCE CLASS™



APPLICATION

The Performance Class OPTI-SELECT Area Light offers 3 CCTs, 3 lumen outputs and 3 light distributions in the same product. With an integrated 7-pin NEMA receptacle and field installable screw-in sensors, this flexible product is ideal for parking lots, walkways and general outdoor area lighting.

BENEFITS & FEATURES

- OPTI-SELECT: Multiple distributions adjustable via switch, no lens swap needed and no screws to remove. Types III, IV and V distribution in the same product
- Up to 150 LPW
- Selectable color temperature: 3000K/4000K/5000K, or the exclusive 1800K/2200K/2700K
- CRI >80
- Selectable wattage and lumens:
 - 40/60/80W | 6,000/9,000/12,000 lm
 - 90/120/150W | 13,500/18,000/22,500 lm
 - 180/240/300W | 27,000/36,000/45,000 lm
- FLEXMOUNT: Universal bracket for slip fitter, wall, round and square pole mounting
- DLC 5.1 Premium Listing assures high energy efficiency and qualifies this product for utility rebates
- Dark Sky compliant in the 1800/2200/2700K version
- Ready for field installable standalone sensors and LEDVANCE LINK™ Bluetooth® Controllers and sensors, no wiring required
- 7-pin NEMA receptacle + shorting cap (optional photocell available as an accessory)



LEDLUM214R9 5-25

SELECTABLE OPTICAL DISTRIBUTION

Innovative Field Adjustment Distribution
T3, T4 and T5 in one product

**NO LENS CHANGE NEEDED; SIMPLY ADJUST THE SWITCH
FOR DESIRED DISTRIBUTION**

OPTISELECT



ELECTRICAL

- 120-347 V_{AC}
(optional 277-480 V_{AC})
- Power Factor >0.9
- THD <20%
- Dimmable 0-10V
- 10kV Surge protection

RATED LIFE

- 100,000 hours (L₇₀) @ 25°C

OPERATING TEMPERATURE

- -40°F to +122°F (-40°C to +50°C)

CERTIFICATIONS & LISTINGS

- cULus listed to UL1598 standards
- RoHs
- FCC
- IP65, wet location
- 3G vibration rated, ANSI C136.31
- DLC 5.1 Premium
- Dark Sky compliant*

*1800/2200/2700 (SC15) version only

WARRANTY

- 5 year
- NLB Trusted Warranty Program

INSTALLATION

- Universal mounting bracket included for square and round pole mounting as well as slip fitter mount



INSTALLATION GUIDE

WATTAGE COMPARISON

LED SOURCE WATTAGE/LUMENS	REPLACES TRADITIONAL SOURCE	ENERGY SAVINGS
90W/12,000lm	HPS/MH	up to 250W
150W/22,500lm		up to 400W
300W/45,000lm		up to 1000W

ORDERING GUIDE

AREAFLD	6A	SXXX	XXX	D	SCX	ADJ	XX
PRODUCT NAME	GENERATION	WATTAGE	VOLTAGE	DIMMING	COLOR TEMPERATURE	DISTRIBUTION	COLOR/ FINISH
AREAFLD = Area Flood	6A = Generation 6A	S080 = 40/60/80W S150 = 90/120/150W S300 = 180/240/300W	UNH = 120-347V HUV = 277-480V	D = 0-10V Dimming	SC2 = 3000/4000/5000K SC15 = 1800/2200/2700K	ADJ = Adjustable T3/T4/T5	BZ = Bronze BL = Black WH = White

*Only SC15 models are Dark Sky approved.

ORDERING INFORMATION

ITEM #	ORDERING ABBREVIATION	WATTAGE (W)	INPUT VOLTAGE (V)	DIM. (V)	CRI	COLOR TEMP (CCT)	DISTRIBU-TION	TOTAL LUMENS (LM)	DLC	LPW	FINISH	MTO*
OPTI-SELECT Adjustable Distribution, Lumen and CCT Selectable												
64012	AREAFLD6AS080UNHDSC2ADJBZ	40/60/80	120-347V	0-10V	>80	3000/4000 /5000K	Adjustable T3/T4/T5	6,000/9,000 /12,000	5.1 Prm	up to 150	Bronze	–
64013	AREAFLD6AS150UNHDSC2ADJBZ	90/120/150	120-347V	0-10V	>80	3000/4000 /5000K	Adjustable T3/T4/T5	13,500/18,000 /22,500	5.1 Prm	up to 150	Bronze	–
64014	AREAFLD6AS300UNHDSC2ADJBZ	180/240/300	120-347V	0-10V	>80	3000/4000 /5000K	Adjustable T3/T4/T5	27,000/36,000 /45,000	5.1 Prm	up to 150	Bronze	–
64087	AREAFLD6AS080UNHDSC15ADJBZ	40/60/80	120-347V	0-10V	>80	1800/2200 /2700K	Adjustable T3/T4/T5	5,040/7,560 /10,080	–	up to 125	Bronze	–
64088	AREAFLD6AS150UNHDSC15ADJBZ	90/120/150	120-347V	0-10 V	>80	1800/2200 /2700K	Adjustable T3/T4/T5	11,340/15,120 /18,900	–	up to 125	Bronze	–
64089	AREAFLD6AS300UNHDSC15ADJBZ	180/240/300	120-347V	0-10V	>80	1800/2200 /2700K	Adjustable T3/T4/T5	22,680/30,240 /37,800	–	up to 125	Bronze	–
66225	AREAFLD6AS080UNHDSC2ADJBL	40/60/80	120-347V	0-10V	>80	3000/4000 /5000K	Adjustable T3/T4/T5	6,000/9,000 /12,000	5.1 Prm	up to 150	Black	–
66226	AREAFLD6AS150UNHDSC2ADJBL	90/120/150	120-347V	0-10V	>80	3000/4000 /5000K	Adjustable T3/T4/T5	13,500/18,000 /22,500	5.1 Prm	up to 150	Black	–
66227	AREAFLD6AS300UNHDSC2ADJBL	180/240/300	120-347V	0-10V	>80	3000/4000 /5000K	Adjustable T3/T4/T5	27,000/36,000 /45,000	5.1 Prm	up to 150	Black	–
66228	AREAFLD6AS080UNHDSC2ADJWH	40/60/80	120-347V	0-10V	>80	3000/4000 /5000K	Adjustable T3/T4/T5	6,000/9,000 /12,000	5.1 Prm	up to 150	White	–
66229	AREAFLD6AS150UNHDSC2ADJWH	90/120/150	120-347V	0-10V	>80	3000/4000 /5000K	Adjustable T3/T4/T5	13,500/18,000 /22,500	5.1 Prm	up to 150	White	–
66230	AREAFLD6AS300UNHDSC2ADJWH	180/240/300	120-347V	0-10V	>80	3000/4000 /5000K	Adjustable T3/T4/T5	27,000/36,000 /45,000	5.1 Prm	up to 150	White	–
66482	AREAFLD6AS080UNHDSC2ADJGR	40/60/80	120-347V	0-10V	>80	3000/4000 /5000K	Adjustable T3/T4/T5	6,000/9,000 /12,000	5.1 Prm	up to 150	Gray	–
66483	AREAFLD6AS150UNHDSC2ADJGR	90/120/150	120-347V	0-10V	>80	3000/4000 /5000K	Adjustable T3/T4/T5	13,500/18,000 /22,500	5.1 Prm	up to 150	Gray	–
66484	AREAFLD6AS300UNHDSC2ADJGR	180/240/300	120-347V	0-10V	>80	3000/4000 /5000K	Adjustable T3/T4/T5	27,000/36,000 /45,000	5.1 Prm	up to 150	Gray	–
66052	AREAFLD6AS080HUVDS2ADJBZ	40/60/80	277-480V	0-10V	>80	3000/4000 /5000K	Adjustable T3/T4/T5	6,000/9,000 /12,000	5.1 Prm	up to 150	Bronze	✓
66053	AREAFLD6AS150HUVDS2ADJBZ	90/120/150	277-480V	0-10V	>80	3000/4000 /5000K	Adjustable T3/T4/T5	13,500/18,000 /22,500	5.1 Prm	up to 150	Bronze	✓
66054	AREAFLD6AS300HUVDS2ADJBZ	180/240/300	277-480V	0-10V	>80	3000/4000 /5000K	Adjustable T3/T4/T5	27,000/36,000 /45,000	5.1 Prm	up to 150	Bronze	✓
66055	AREAFLD6AS080HUVDS15ADJBZ	40/60/80	277-480V	0-10V	>80	1800/2200 /2700K	Adjustable T3/T4/T5	5040/7560 /10,080	–	up to 125	Bronze	✓
66056	AREAFLD6AS150HUVDS15ADJBZ	90/120/150	277-480V	0-10V	>80	1800/2200 /2700K	Adjustable T3/T4/T5	11,340/15,120 /18,900	–	up to 125	Bronze	✓
66057	AREAFLD6AS300HUVDS15ADJBZ	180/240/300	277-480V	0-10V	>80	1800/2200 /2700K	Adjustable T3/T4/T5	22,680/30,240 /37,800	–	up to 125	Bronze	✓
66363	AREAFLD6AS080HUVDS2ADJBL	40/60/80	277-480V	0-10V	>80	3000/4000 /5000K	Adjustable T3/T4/T5	6,000/9,000/ 12,000	5.1 Prm	up to 150	Black	✓
66364	AREAFLD6AS150HUVDS2ADJBL	90/120/150	277-480V	0-10V	>80	3000/4000 /5000K	Adjustable T3/T4/T5	13,500/18,000 /22,500	5.1 Prm	up to 150	Black	✓
66365	AREAFLD6AS300HUVDS2ADJBL	180/240/300	277-480V	0-10V	>80	3000/4000 /5000K	Adjustable T3/T4/T5	27,000/36,000 /45,000	5.1 Prm	up to 150	Black	✓
66360	AREAFLD6AS080HUVDS2ADJWH	40/60/80	277-480V	0-10V	>80	3000/4000 /5000K	Adjustable T3/T4/T5	6,000/9,000 /12,000	5.1 Prm	up to 150	White	✓
66361	AREAFLD6AS150HUVDS2ADJWH	90/120/150	277-480V	0-10V	>80	3000/4000 /5000K	Adjustable T3/T4/T5	13,500/18,000 /22,500	5.1 Prm	up to 150	White	✓
66362	AREAFLD6AS300HUVDS2ADJWH	180/240/300	277-480V	0-10V	>80	3000/4000 /5000K	Adjustable T3/T4/T5	27,000/36,000 /45,000	5.1 Prm	up to 150	White	✓
66509	AREAFLD6AS080HUVDS2ADJGR	40/60/80	277-480V	0-10V	>80	3000/4000 /5000K	Adjustable T3/T4/T5	6,000/9,000 /12,000	5.1 Prm	up to 150	Gray	✓
66510	AREAFLD6AS150HUVDS2ADJGR	90/120/150	277-480V	0-10V	>80	3000/4000 /5000K	Adjustable T3/T4/T5	13,500/18,000 /22,500	5.1 Prm	up to 150	Gray	✓
66511	AREAFLD6AS300HUVDS2ADJGR	180/240/300	277-480V	0-10V	>80	3000/4000 /5000K	Adjustable T3/T4/T5	27,000/36,000 /45,000	5.1 Prm	up to 150	Gray	✓

*Made to Order

BUG RATING


WATTAGE	T3	T4	T5
80	B2-U0-G2	B3-U0-G3	B3-U0-G2
150	B3-U0-G3	B4-U0-G4	B4-U0-G3
300	B4-U0-G4	B5-U0-G5	B5-U0-G4

PHYSICAL INFORMATION


LUMINAIRE DESCRIPTION	LENGTH IN (MM)	WIDTH IN (MM)	HEIGHT IN (MM)	WEIGHT LB (KG)	EPA* (FT²) TILT ANGLE		
					0° (HORIZONTAL)	≤45°	≤90° (VERTICAL)
80W OPTI-SELECT	25.9 (657)	10.6 (270)	6.3 (160)	13.1 (6.0)	0.20	0.90	1.52
150W OPTI-SELECT	30 (764)	13.5 (342)	6.3 (160)	16.7 (7.6)	0.23	1.42	2.41
300W OPTI-SELECT	33.4 (848)	15.8 (402)	6.3 (160)	21.1 (9.6)	0.26	1.92	3.26

*Considering horizontal wind


OPTI-SELECT 80W



OPTI-SELECT 150W




OPTI-SELECT 300W




UNIVERSAL MOUNTING BRACKET

- Included with each luminaire
- SC15 versions include a slip fitter with limited adjustability for Dark Sky compliance.



POLE DRILL PATTERN




ACCESSORIES

ITEM #	ORDERING ABBREVIATION	ITEM DESCRIPTION
Visors		
66188	AREAOPTISELECTSMVISORFBBZ	Small visor, front or back, bronze (for 80W)
66189	AREAOPTISELECTMEDVISORFBBZ	Medium visor, front or back, bronze (for 150W)
66190	AREAOPTISELECTLRGVISORFBBZ	Large visor, front or back, bronze (for 300W)
66191	AREAOPTISELECTSMVISORLRBZ	Small visor, left or right, bronze (for 80W)
66192	AREAOPTISELECTMEDVISORLRBZ	Medium visor, left or right, bronze (for 150W)
66193	AREAOPTISELECTLRGVISORLRBZ	Large visor, left or right, bronze (for 300W)
66348	AREAOPTISELECTSMVISORFBBL	Small visor, front or back, black (for 80W)
66349	AREAOPTISELECTMEDVISORFBBL	Medium visor, front or back, black (for 150W)
66350	AREAOPTISELECTLRGVISORFBBL	Large visor, front or back, black (for 300W)
66351	AREAOPTISELECTSMVISORLRBL	Small visor, right or left, black (for 80W)
66352	AREAOPTISELECTMEDVISORLRBL	Medium visor, right or left, black (for 150W)
66353	AREAOPTISELECTLRGVISORLRBL	Large visor, right or left, black (for 300W)
66354	AREAOPTISELECTSMVISORFBWH	Small visor, front or back, white (for 80W)
66355	AREAOPTISELECTMEDVISORFBWH	Medium visor, front or back, white (for 150W)
66356	AREAOPTISELECTLRGVISORFBWH	Large visor, front or back, white (for 300W)
66357	AREAOPTISELECTSMVISORLRWH	Small visor, right or left, white (for 80W)
66358	AREAOPTISELECTMEDVISORLRWH	Medium visor, right or left, white (for 150W)
66359	AREAOPTISELECTLRGVISORLRWH	Large visor, right or left, white (for 300W)
Yoke Mounting		
66528	AREAFLDOSYOKE80WBZ	Yoke mount for 80W, Bronze
66529	AREAFLDOSYOKE150WBZ	Yoke mount for 150W, Bronze
66530	AREAFLDOSYOKE300WBZ	Yoke mount for 300W, Bronze
Wall Mounting Brackets		
61174	BRACKET1AWALLHORIZTENONBZ	Horizontal wall mounting bracket, Bronze
61175	BRACKET1AWALL90DEGTENONBZ	90° wall mounting bracket, Bronze
Sensors		
62664	HIGHBAYPIRMOTIONDAYSENSOR2	Field installable PIR Motion/Daylight Sensor, IP65, Max. mounting height 39ft, White
65622*	HIGHBAYMOTIONDAYSENSOR	Field installable Microwave Motion/Daylight Sensor, IP65, Max. mounting height 49ft, White
65623	REMOTE/MOTIONDAY/001	Remote control for Motion/Daylight Sensors – Remote is required to change default settings
Photocells		
61393	AREAFLDXANEMAPHOTOCELLUNV	Area/Flood NEMA photocell 120-277V
64258	AREAFLDXANEMAPHOTOCELLHUV	Area/Flood NEMA photocell 347-480V
63197	NEMASHORTINGCAP	NEMA Shorting cap (base unit already ships with shorting cap)


*Microwave sensors are not recommended for outdoor use. Microwave sensors are highly sensitive. Metal, glass, windows, industrial fans, and large obstructions can all generate false triggering. Based on installation, PIR sensor may be a better option, although extreme heat or cold can reduce sensitivity or cause false triggers. For additional application notes, please go to: <https://assets3.ledvanceus.com/media/resource/original/asset-13239171>

ITEM #	ORDERING ABBREVIATION	ITEM DESCRIPTION
LEDVANCE LINK™ Accessories		
63652	SENSORADAPTER1A	Sensor adapter for LEDVANCE LINK™ sensors
75913	SENSOR2ODPIR3.5BLEBLK	Outdoor Bluetooth® Low Energy Mesh PIR sensor with controller, Screw-in Plug & Play, 3.5mm AUX, Black


80W VISOR




150W VISOR




300W VISOR




80W YOKE MOUNTING BRACKET



150W YOKE MOUNTING BRACKET




300W YOKE MOUNTING BRACKET




WALL BRACKET

61174



61175



Brackets
Spec Sheet



OPTIONAL MOTION/DAYLIGHT SENSOR DEFAULT SETTINGS

Detection Area	100%
Hold time – Time fixtures stays at 100% after last motion before dimming	10 minutes
Daylight threshold – Light level above which lights will remain off	50 Lux
Stand-by period – Time light remains dimmed before shutting off	60 minutes
Stand-by Dimming – dimming level of light during the stand-by period	30%



**MOTION SENSOR
(62664)**



**REMOTE
(65623)**

OPTIONAL LEDVANCE LINK™ ACCESSORIES (COMING SOON)



LINK Wireless Control



**BLUETOOTH® MESH
WIRELESS CONTROLLER
& SENSOR, LEDVANCE
LINK™ (75913)**



**SENSOR
ADAPTER FOR
LEDVANCE LINK™
SENSORS**

BENEFITS & FEATURES

- The LEDVANCE LINK™ Bluetooth® Mesh Low Voltage components use Bluetooth® technology for easy and secure wireless communication
- Enables regular LEDVANCE luminaires to become Bluetooth® enabled and allows for luminaires to be turned on/off and dimmed (manual or auto)
- Components can be used up to 40ft fixture mounting height
- Control using either the LEDVANCE LINK™ app or the wireless/wired wall controller

SENSOR INFORMATION


- Photocell Threshold On/Off + PIR sensing technology
- Input voltage: 12Vdc
- Bluetooth® transmission range: 328ft max.
- Detection range: 48-80ft
- Input current: 50mA
- Dimming: 0-10V
- Mounting height: 20-40ft
- Operating temperature: -22°F~131°F (-30°C~55°C)
- IP rating: IP66, wet rated
- Protocol: Bluetooth® Mesh BLE Proprietary




COMMISSIONING
GUIDE

MOUNTING HEIGHT: UP TO 40'

Detection Coverage Side View



Detection Coverage Top View



Download on the
App Store




GET IT ON
Google Play


PHOTOMETRIC INFORMATION

HORIZONTAL ISO FOOT-CANDLE PLOT


80W luminaire, T3 distribution, mounted at 25' height




80W luminaire, T4 distribution, mounted at 25' height




80W luminaire, T5 distribution, mounted at 25' height




150W luminaire, T3 distribution, mounted at 30' height




150W luminaire, T4 distribution, mounted at 30' height




150W luminaire, T5 distribution, mounted at 30' height




300W luminaire, T3 distribution, mounted at 40' height



300W luminaire, T4 distribution, mounted at 40' height



300W luminaire, T5 distribution, mounted at 40' height



MOUNTING HEIGHT (FT)	15	20	25	30	35	40
MULTIPLIER	4.00	2.25	1.44	1	0.73	0.56

MOUNTING HEIGHT (FT)	25	30	35	40	45	50
MULTIPLIER	2.56	1.78	1.31	1	0.79	0.64

- Multiply the footcandle levels in the diagram according to the desired installation height
- Each tick on the diagram represents a multiple of the mounting height from the fixture



LEDVANCE LLC
181 Ballardvale Street, Suite 203
Wilmington, MA 01887 USA
Phone: 1-800-LIGHTBULB (1-800-544-4828)
www.ledvanceUS.com

LEDVANCE is a registered trademark.
The Bluetooth® word mark and logos are registered
trademarks owned by the Bluetooth SIG, Inc. and any
use of such marks by LEDVANCE LLC is under license.
All other trademarks are those of their respective owners.
Specifications subject to change without notice.



SCAN TO FOLLOW US
ON SOCIAL MEDIA