


Item Number **5310000**

11R/4"/LED/DIM/SLIM/FL/FR/27-50

Specifications

- 2-Hour Fire Rating with fire-proof housing
- Complies with ASTM E119, UL 263 and CAN/ULC 101 Testing and Certified for 2 Hours
- Energy Used (Watts): 11
- Incandescent Equivalent Wattage: 80
- Volts: 120
- Baffle: Smooth
- Brightness (Lumens): 900
- Average Rated Hours: 50000
- Beam Spread: 110°
- Beam Type: Flood
- CRI: 90
- Efficacy (LPW): 82
- Estimated Yearly Energy Cost**: \$1.32
- Package Type: Black and White Box
- Meets air-tight requirements
- Use with a two-hour fire-rated floor/ceiling assembly constructed in accordance with material and construction specifications of UL Design No. UL 505, L511, L536, L538, L541, L556, L577, M500, M510, M521, or M543



Physical Characteristics

- Color Designation: Multi: 2700, 3000, 3500, 4000, 5000
- Finish: White
- Housing Material: Steel
- Base: Recess Mounting
- MOL: 2.32"
- MOD: 5.04"



Limited Warranty

5 Year

For full warranty information, please follow this link:

www.westinghouselighting.com/pdfs/warranty-cards/ES-WH-001-W.pdf

Warning

- Turn power off before inspection, installation, or removal.
- Suitable for wet locations - The product is suitable for use in wet locations.
- Do not open - no user serviceable parts inside.
- This device is not intended for use with emergency exit luminaires or emergency exit lights.
- This device complies with Part 15 of the FCC rules and has been tested and found to comply with the limits for a Class B digital device. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to the radio communication. Any changes or modifications not expressly approved by the manufacturer could avoid the user's authority to operate the equipment.
- This product may not be compatible with all dimmers.



Can be used to comply with the 2025 Title 24, Part 6 high-efficacy light source requirements; where applicable install a Title 24 compliant light bulb (sold separately) to fill each socket.

Specifications are subject to change without notice, please visit www.westinghouselighting.com for latest information.

® and Westinghouse are trademarks of Westinghouse Electric Corporation.
Used under license by Westinghouse Lighting. All Rights Reserved.

** Based on 3hrs./day 11¢/kWh - Cost depends on rates and use.

Item Number 5310000**Compatible Dimmers**

Brand	Model
Lutron	DVCL-153P, DVCL-253P, DVCL-253P-WH, MACL-153M, MRF2-6CL, PD-6WCL, S-600, SCL-153P, TGCL-153P
Leviton	DDL06-1LZ, DL1KD, DL6HD, DW1KD, DW6HD, DDMX1-BLZ, C22-6672-1LW, C26-RNL06-TW, R62-6683-IW, R62-6674-POW, 002-6674-10W, 001-RDL06-10Z, 011-IPL06-10Z, 012-TSL06-1LW, 001-RNL06-10Z, 001-DLS06-1LZ
Cooper	DAL06P-C1

Specifications are subject to change without notice, please visit www.westinghouselighting.com for latest information.

 and Westinghouse are trademarks of Westinghouse Electric Corporation.
Used under license by Westinghouse Lighting. All Rights Reserved.