



SmartMate

SMARTMATE ELE BALLAST (2) 26W CFL (4-PIN) 120-277V

Offering maximum versatility, the Philips Advance family of SmartMate ballasts for 4-pin compact fluorescent lamps drive a broad range of quad and triple-tube, circline, 2D, and long twin-tube lamps. SmartMate ballasts' energy efficient design, compact and lightweight housing, and user-friendly features make these ballasts an ideal choice for fixture manufacturers, retrofitters, and MRO replacement.

Product data

General Information				
Lamp Type	CFQ26W/G24Q			
Number of Lamps	1/2 piece/unit			
Ballast Type	Electronic Fluorescent			
Base Model	ICF2S26M1BS			
Suitable For Outdoor Use	Yes			
Automatic Restart	Yes			
Operating and Electrical				
Input Voltage	120 to 277 V			
Input Frequency	50 to 60 Hz			
Max THD	10 %			
Starting Method	Programmed Start			
Lamp Current Crest Factor (Nom)	1.5			
Ignition Time (Nom)	1.5 s			
Ballast Factor (Nom)	1			
Power Factor (Nom)	0.98			
Input Current (Operating) (Max)	0.43 A			
Input Current (Operating) (Min)	0.19 A			
Input Power (Nom)	51-51 W			

Rated Lamp Watts	26 W
Wiring	
Color Input Terminals	BLK & WHT
Color Output Terminals	RED, YEL & BLU
Wire Striplength	0.375 mm
Lamp Connection	Series
Wire Length by Color	No wires
Wire Gauge (Nom)	18AWG mm
Wire Type	Solid
Remote Wiring Configuration Allowed	Yes
Tandem Wiring Configuration Allowed	Yes
Through Wiring Configuration Allowed	Yes
Max Ballast-Lamp Distance Remote Wiring	1-L = 15' / 2-L = 6'
Max Ballast-Lamp Distance Tandem Wiring	2-L: Red = 6'
Max Ballast-Lamp Distance Through Wiring	2-L: Red = 6'
Connector Type	Poke-In
Temperature	
T-Case Maximum (Nom)	75 °C


Datasheet, 2017, November 6 data subject to change

SmartMate

Mechanical and Housing		
Housing Material	Metal	
Housing	M1	
Housing Dimensions	4.98" x 2.4" x 0.98"	
Approval and Application		
EMC Immunity Standard	FCC Non-Consumer	
Approbation Marks	CSA certificate UL certificate CEC Listing RoHS	
	Compliant	
Sound Rating	A	
UL Recognized	No	

Product Data	
Order product name	SMARTMATE ICF2S26M1BS35M
EAN/UPC - Product	781087108307
Order code	ICF2S26M1BS35M
lumerator - Quantity Per Pack	1
umerator - Packs per outer box	16
Material Nr. (12NC)	913700532401
Net Weight (Piece)	0.215 kg

Dimensional drawing



SMARTMATE ICF2S26M1BS35B

Product	A1	A2	A3	B1	C1
SMARTMATE ICF2S26M1BS35M	4.60 in	4.20 in	2.00 in	2.40 in	0.98 in

