



SmartMate

SMARTMATE ELE BAL (2) 13W CFL (4-PIN) 120-277V KIT

Offering maximum versatility, the Philips Advance family of SmartMate ballasts for 4-pin compact fluorescent lamps drive a broad range of quad and triple-tube, circline, 2D, and long twin-tube lamps. SmartMate ballasts' energy efficient design, compact and lightweight housing, and user-friendly features make these ballasts an ideal choice for fixture manufacturers, retrofitters, and MRO replacement.

Product data

General Information	
Lamp Type	CFQ13W/G24Q
Number of Lamps	1/2 piece/unit
Ballast Type	Electronic Fluorescent
Base Model	ICF2S13H1LD
Suitable For Outdoor Use	Yes
Automatic Restart	Yes
Operating and Electrical	
Input Voltage	120 to 277 V
Input Frequency	50 to 60 Hz
Max THD	10 %
Starting Method	Programmed Start
Lamp Current Crest Factor (Nom)	1.5
Ignition Time (Nom)	1.5 s
Ballast Factor (Nom)	1
Power Factor (Nom)	0.98
Input Current (Operating) (Max)	0.25 A
Input Current (Operating) (Min)	0.11 A
Input Power (Nom)	29-29 W

Rated Lamp Watts	13 W		
Wiring			
Color Input Terminals	BLK & WHT		
Color Output Terminals	RED, YEL & BLU		
Wire Striplength	0.375 mm		
Lamp Connection	Series		
Wire Length by Color	No wires		
Wire Gauge (Nom)	18AWG mm		
Wire Type	Solid		
Remote Wiring Configuration Allowed	Yes		
Tandem Wiring Configuration Allowed	Yes		
Through Wiring Configuration Allowed	Yes		
Max Ballast-Lamp Distance Remote Wiring	1-L = 15' / 2-L = 6'		
Max Ballast-Lamp Distance Tandem Wiring	2-L: Red = 6'		
Max Ballast-Lamp Distance Through Wiring	2-L: Red = 6'		
Connector Type	Poke-In		
Temperature			
T-Case Maximum (Nom)	75 °C		


Datasheet, 2017, November 6 data subject to change

SmartMate

Mechanical and Housing			
Housing Material	Metal/Plastic		
Housing	H1		
Housing Dimensions	4.98" x 2.4" x 0.98"		
Approval and Application			
EMC Immunity Standard	FCC Non-Consumer		
Approbation Marks	CSA certificate UL certificate CEC Listing NOM		
	certificate RoHS Compliant		
Sound Rating	A		
UL Recognized	No		

Product Data				
Order product name	SMARTMATE ICF2S13H1LDK			
EAN/UPC - Product	781087117750			
Order code	ICF2S13H1LDK			
Numerator - Quantity Per Pack	1			
Numerator - Packs per outer box	12			
Material Nr. (12NC)	913700500811			
Net Weight (Piece)	0.250 kg			

Dimensional drawing



ELE BAL (2) 13W CFL (4-PIN) 120-277V KIT

Product	A1	A2	A3	B1	C1
SMARTMATE ICF2S13H1LDK	4.60 in	4.20 in	2.00 in	3.00 in	1.29 in

