



Features

- Slim and compact 24V DC constant voltage hardwire driver
- Dedicated line voltage and low voltage wiring compartments
- Multiple 7/8" knock-outs for easy wire configuration
- Short circuit, over-voltage, over-temperature, overload protections
- 5-in-1 Forward and Reverse Phase Dimming: ELV, MLV, TRIAC, 0-10V, 1-10V, 10V PWM Potentiometer
- cULus Listed Wet location rated
- Class 2, Type HL, FCC Compliant

Wattage/Voltage Options

- 288W (24V DC)

Dimming Options

- Phase (ELV, MLV, TRIAC)/0-10V/1-10V/10V PWM Potentiometer

Listing / Ratings



Adaptive PRO - 288W

The Adaptive Pro 5-in-1 dimmable Class 2 drivers are designed to operate with any standard MLV, ELV, Incandescent TRIAC (forward phase) dimmer switch or can also be used with secondary side controls systems. Encased in a low profile aluminum enclosure that includes knock-outs for easy installation in any low voltage application.

Technical Information

Series	ADPTPRO-DRJ 288W
Max Load	288W (3 x 96W)
Minimum Load	3 x 9.6W
Input Voltage	100-277V AC
Output Voltage	24V DC
Dimmable	Phase (ELV, MLV, TRIAC)/0-10V/1-10V/10V PWM Potentiometer
Efficiency	> 87% (120V), 91% (277V)
Operating Temp.	-40°F to 140°F (-40°C to 60°C)
Rating	cULus Listed for wet locations
Dimensions	11.29"L x 4.33"W x 1.88"H

Ordering Information

ADPTPRO-DRJ-288-24 Adaptive Pro 24V DC - 288W (3 x 96W) Power Supply