

MICROLUX RGB

24V DC Diffuse Flexible LED

Featuring fully encased tape light, MicroLux provides smooth evenly diffused light that eliminates the needs for additional extrusion housings and lenses. With light emitting from three sides, MicroLux is a unique product that can be used in small spaces, or be placed on in direct view to meet the needs of dynamic lighting installations.

- Fully encased design eliminates dotting and provides diffused lighting
- Eliminates the need for additional extrusion housings and lenses
- Full RGB color mixing produces 16 million colors
- Features top-bend flexibility
- Cuttable every 3.94"
- Dimmable with ELV dimming drivers & Trulux Lighting controls
- Maximum runs up to 16.4 feet
- IP65 rating (encased) for indoor & outdoor use
- cULus Listed - 50,000 hours rated life



MICROLUX RGB QUICK SPECS


VOLTAGE	24V
WATTAGE	4.4W / ft
LUMENS	170Lm / ft
CCT	RGB
CRI	N/A
MAX RUN	16.4ft
CUTTING POINTS	3.94" (100mm)
IP RATING	IP65 - Wet Location
DIMMING	5-100%
DIMENSIONS	0.37" (9.5mm) W x 5/16" (8mm) H
BEAM ANGLE	120°
CERTIFICATIONS	cULus Listed
RATED LIFE	50,000 Hours

PROJECT:



TYPE:

LOCATION:

CATALOG NUMBER:




MICROLUX RGB QUICK LOOK



IP65 (Encased)

Features a clear protective silicone jacketing that protects the tape light from sprayed water and dust.
Best suited: Indoor & Outdoor damp & wet locations

MICROLUX RGB QUICK SET-UP




RGBW Controller
(3 zone)



Adaptive Series Power Supply
(30W / 60W / 96W / 192W / 288W)



Decoder/Receiver
(Required per zone)



MicroLux

MICROLUX RGB ORDERING INFORMATION

ITEM NUMBER	VOLTAGE	CCT	LENGTH	LUMENS / FT	WATTAGE / FT	IP RATING	CRI	CUTTING	MAX RUN
MLUX-RGB	24V	RGB	16.4 ft	170Lm / ft	4.4W / ft	IP65	N/A	3.94" (100mm)	16.4 ft


MLUX-RGB includes: Attached 3ft Lead Wire / (15) Mounting Clips

MICROLUX RGB ACCESSORIES

ITEM NUMBER	DESCRIPTION
MLUX-CONKIT4	RGB Power Feed
MLUX-END	End Cap (QTY 10)
MLUX-CLIPS	Mounting Clips (QTY 10)
MLUX-CHAN-3A	1M Deep Mounting Channel
MLUX-CHAN-3B	1M Shallow Mounting Channel
RCWY-PVC-1M	1m Plastic Wire Cover Raceway



MLUX-CONKIT4



MLUX-END



MLUX-CLIPS



MLUX-CHAN-3A



MLUX-CHAN-3B



RCWY-PVC-1M

RECOMMENDED POWER SUPPLIES

ITEM NUMBER	DESCRIPTION	MAX / MIN LOAD	INPUT VOLTAGE	OUTPUT VOLTAGE	DIMMABLE	DIMENSIONS
PZM-ADPT-DRJ-30-24	Adaptive Series 30W	30W / 3W	100-277V AC	24V DC	Yes*	6.49"L x 3.6"W x 1.02"H
PZM-ADPT-DRJ-60-24	Adaptive Series 60W	60W / 6W	100-277V AC	24V DC	Yes*	7.4"L x 3.6"W x 1.02"H
PZM-ADPT-DRJ-96-24	Adaptive Series 96W	96W / 9.6W	100-277V AC	24V DC	Yes*	8.66"L x 3.6"W x 1.61"H
PZM-ADPT-DRJ-192-24	Adaptive Series 192W (2 x 96W)	192W / 19.2W	100-277V AC	24V DC	Yes*	10.94"L x 4.25"W x 1.8"H
PZM-ADPT-DRJ-288-24	Adaptive Series 288W (3 x 96W)	288W / 28.8W	100-277V AC	24V DC	Yes*	11.85"L x 4.25"W x 1.8"H

Phase Dimming Compatible With Most MLV, ELV, and TRIAC Dimmers



AMERICAN LIGHTING WARRANTY

LIMITED WARRANTY FOR LED PRODUCTS: 3 YEARS

LIMITED PRODUCT WARRANTY

Our products are warranted to be free from defects in material and workmanship for the warranty period listed. Warranty periods begin from the date of shipment from American Lighting Inc's warehouse to the original purchaser. Products that prove to be defective during their specific warranty period will be either repaired or replaced, at the sole discretion of American Lighting Inc. Claims for defective products must be submitted in writing to American Lighting Inc's RGA Department within the warranty period. Upon approval of such return, American Lighting Inc reserves the right to inspect the product for misuse or abuse. Claims for indirect or consequential damages or for product that, in American Lighting Inc's opinion, has been misused will be denied. This is a warranty of product reliability only and not a warranty of merchantability or fitness for a particular purpose. American Lighting Inc shall have no liability whatsoever in any event for payment of incidental or consequential damages, including, without limitations, installation costs and/or damages for personal injury and/or property. These products may represent a possible shock or fire hazard if improperly installed or altered in any way. This warranty does not apply to any product that has not been properly installed in accordance with current local codes and/or the National Electrical Code. Products that require a transformer, driver, or power supply must be used in conjunction with American Lighting Inc's recommended power supply to ensure safety and retain product warranty.

PRODUCT SPECIFICATIONS

For the latest product information, updates, instructions and details concerning specifications, colors, finishes, performance, installation and design, visit www.americanlighting.com.

Color may vary from the color printed herein due to limitations in photographic and printing processes. American Lighting Inc. reserves the right to change product specifications without notice. Other product specifications such as color temperature, wavelength characteristics and lumen output are subject to production limitations and may vary.

LED technology is changing rapidly, and not all color temperatures and performance levels can be duplicated at a later time. Best practices include purchasing 10-15% more for a particular project on the same initial order where white LED color temperatures must be maintained over project and product life. Eventual product replacement should be considered at layout and design stages. Best practices also include testing connections and product performance prior to mounting and/or installing.

AVERAGE LIFE

Average incandescent lamp life, rated life and average life are terms used to describe the number of hours at which half of the lamps have failed. For LEDs, the hours of rated life specify the point where 70% of original lumen output is reached. Below this point, the effective life is over, however, the LED may still emit light. Individual results may vary with actual environmental conditions including, but not limited to, proper installation, ambient temperature and/or input voltage fluctuations.