# HYBRID 2 KITS

Line voltage Hybrid 2 Kits are economical - no drivers needed - and link up to 150 feet. Interconnect multiple cETLus rated kits for high output applications, indoors and out.

#### Performance

- 120° beam angle provides even light distribution perfect for coves and numerous accent lighting applications
- 5050 SMD LEDs emit up to 180 lumens per foot
- Dimmable with most incandescent, low voltage magnetic and low voltage electronic dimmers\* (minimum loads may apply)
- Available in Bright White (5000K) and Warm White (2700K), in six interconnectable lengths that quickly twist and connect together, up to 150 feet

#### Construction

- Kits include a 5ft removable power cord, one removable end cap and one mounting clip per foot of length
- Flexible housing with clear PVC lens is protected with UV inhibitor
- Parallel wiring to each LED improves longevity

#### Installation

- Use clips to hold in place for most cove applications
- Clear plastic track or aluminum channel should be used when straight lines of light are needed or when mounting to the underside of a shelf or ledge to prevent sagging





## Specifications

Series	H2-KIT
Input voltage	120V AC, 60Hz
Colors	2700K (WW) / 5000K (WH)
CRI	82
Wattage	3W/ft
Lumens	145Lm/ft (WW) / 180Lm/ft (WH)
Kit lengths	3ft, 6ft, 12ft, 18ft, 30ft, & 45ft
Maximum run	150 feet
Cuttability	N/A
Beam angle	120°
Dimming	10-100% with most dimmers*
Material	Clear PVC face, white back
Rating	cETLus Listed for wet locations**
Dimensions	9/16"W x 1/4"H
Switching	Wall control
Mounting	Clips, track, or channel
Linking	See jumpers on facing page
LED type	5050 SMD LEDs (20 per foot)
Rated life	30,000 hrs

<sup>\*</sup>Per the NEC, switched wall outlets cannot be used with wall dimmers \*\*c/ETL/us Listing is void if product or its power cord is cut or altered

## Hybrid 2 Kits



H2-KIT-3-WW (3ft length, 9W) **H2-KIT-6-WW** (6ft length, 18W) **H2-KIT-12-WW** (12ft length, 36W) **H2-KIT-18-WW** (18ft length, 54W) **H2-KIT-30-WW** (30ft length, 90W) **H2-KIT-45-WW** (45ft length, 135W) 2700K Warm White LEDs 120V, 82 CRI, 145Lm/ft



H2-KIT-3-WH (3ft length, 9W) H2-KIT-6-WH (6ft length, 18W) **H2-KIT-12-WH** (12ft length, 36W) **H2-KIT-18-WH** (18ft length, 54W) **H2-KIT-30-WH** (30ft length, 90W) **H2-KIT-45-WH** (45ft length, 135W) 5000K Bright White LEDs 120V, 82 CRI, 180Lm/ft

### Hybrid 2 Kit Accessories



**H2-KIT-JUMP.5** 6in jumper cable H2-KIT-JUMP3 3ft jumper cable **H2-KIT-JUMP6** 6ft jumper cable Jumper (linking) cable with twist-and-tighten connecters; jumpers are inter-connectable



H2-TRACK-3 3ft clear plastic mounting track 5/8W x 5/16"H Sold in packs of 10 only



H2-CHAN-3 3ft aluminum mounting track 5/8W x 5/16"H Sold in packs of 10 only