

Save up to
18% of
your home
energy
costs

PowerCost Monitor™

THINK GREEN • ACT SMART • SAVE ENERGY



*The power of information
— the PowerCost Monitor™
BLI 28000 provides real-
time information on energy
consumption and cost.*

Numerous independent research studies have confirmed that most families using the PowerCost Monitor™ BLI 28000 have experienced energy use reduction of up to 18%.

- Read moment to moment energy use and costs
- Measure how much energy is being consumed by specific appliances
- Based on current usage, predict 30 days of energy use and cost
- Track cumulative information — reset as frequently as you wish

What's unique about the PowerCost Monitor™ BLI 28000 from Blue Line Innovations:

- Portable, wireless monitor
- Sensor passively attaches to the outside meter
- No interference and no electrician required
- 130,000+ customers in United States and Canada
- Active Programs with 90+ utilities and numerous research projects completed
- On the market since 2004
- Founder, pioneer and leader in real-time energy feedback
- Displays energy in Kw and \$s
- Programmable for local utility rates — flat, multi-tiered, on/off peak
- Displays time and outside temperature (°F or °C)
- Includes 4 AA Batteries



Note: Compatible with most meters. For more complete information, talk to your authorized retailer or visit www.bluelineinnovations.com

BLUEline
INNOVATIONS



Blue Line Innovations PowerCost Monitor™

Specifications

PowerCost Monitor

- Part # BLI 28000

- Package Unit Weight: 1.7 lbs (.75kg)

- Width: 8.3 in (21.1 cm)

- Height: 8.5 in (21.6 cm)

- Depth: 4 in (10.2 cm)

Master Carton (16 units)

- Package Unit Weight: 32.3 lbs (14.65kg)

- Width: 18 in (45.7 cm)

- Height: 19 in (48.2 cm)

- Depth: 18 in (45.7 cm)

Power Requirements

- Sensor: Standard - 2 alkaline AA 1.5 volt (LR6 type)

Extreme cold weather - 2 lithium AA 1.5 volt (L91 type)

- Display: Standard 2 alkaline AA 1.5 volt (LR6 type)

Communication Range

- Frequency: 433 MHz

- Range: approximately 30m (100 ft) - subtract 5m (15ft) for each wall between sensor and monitor

- Updates from Sensor to Display Unit: every 30 seconds

Operating Temperature

- Display Unit: 10°C to 45°C (50°F to 113°F)

- Sensor Unit: -40°C to 60°C (-40°F to 140°F)

Warranty

- 1 year material defects or workmanship.

Replacement or refund at manufacturer's discretion

Accuracy

- $\pm 1\%$ at meter

Meter Types

- Compatible with most traditional electromechanical disc meters, digital meters, AMR, AMI and Smart Meter technologies.

See www.bluelineinnovations.com for additional information.

- kH factor setting 0.1 - 99.9

Support

- Consumer - 1-866-605-2583, Level 1 information, Level 2 technical

- Direct access for authorized retailer - 1-866-261-7969 ext. 205

BLI-28000-R01

BLUE LINE INNOVATIONS INC.

187 Kenmount Road
1st Floor, ICON Building
St. John's, NL Canada, A1B 3P9

support@bluelineinnovations.com
www.bluelineinnovations.com
Toll free: 1-866-607-2583

