## LED PAR30







Electrical	
Watt	19.8
Power Factor	> 0.9
Voltage	120-277 volt
Frequency	60Hz
Base Type	E26 Medium
Operating Temperature Range	-4F to 104F
Light	
Initial Lumens	2300
Lumens per Watt	116
Color Temperature	3000K
Color Rendering (CRI)	80+
Beam Angle	25°
Agency Approvals	
UL	Yes
Rated Hours	40,000 hours
RoHS	Yes
FCC	Yes
Product Details	
Warranty	5 years
Diameter	3.78"
Nominal Length	4.45"

## PRODUCT DESCRIPTION

19.8 watt PAR30 EarthBulb LED floodlight replaces 75 watt incandescent floodlights for over 85% energy savings. This PAR30 combines high lumen output and energy efficiency. High power LED and an advanced cooling system provides for 40,000 hours of LED life. Medium screw base. Wet location rated. Dimmable when used on 120VAC.

## PRODUCT FEATURES

- Dimming when used on 120VAC
- PAR30 flood light provides 2300 lumens
- · 25° beam angle provides a flood, not spot light
- Unique LED array design look like halogen when powered on
- Super Bright 2x brighter
- Wet rated UL and suitable for exterior locations
- · Fits track heads like a PAR lamp is intended

## PRODUCT APPLICATIONS

- · Architectural Track Lighting
- · Recessed & Decorative Lighting
- · High-End Residential & Office Environments
- Mezzanines
- · House of Worship
- · Specialty Retail Shops







MODEL NUMBER: LP3203025HO

**ORDER CODE: 11267** 

Order Code	Individual UPC	Master Park UPC	Qty
11267	840791112670	84079111267000	12
Dimensions (inches - Length x Width x Height)			
11267	3.86 x 3.86 x 5.12	16.23 x 12.32 x 6.18	12
Weight (lbs)			
11267	.449	6.622	12

