



DWR Downlight Wafer Remote

HIGHLIGHTS

- Easily installs into drywall or suspended ceilings
- Includes remote driver/junction box
- Canless design
- Available in 3 sizes; 4", 6", 8"
- PowerSet models feature multiple wattages in one fixture
- FieldCCeT models feature multiple color temperature settings in one fixture

CERTIFICATIONS

- ETL Listed for US & Canada
- RoHS Compliant
- IC Rated
- Wet Location Rated

PERFORMANCE

- High Efficacy, up to 100 lm/W
- Available in fixed wattage models and PowerSet models
- Available in single CCT models: 3000K or FieldCCeT models: field-selectable CCT 27/30/35/40/5000K
- CRI: >80
- Estimated lifetime: L70: >50,000 hours

ELECTRICAL

- Input voltage: 120V
- Triac dimming to 10%
- Power Factor: >0.9
- THD: <20%

THERMAL

- -4°F to 104°F (-20°C to 40°C) operating temperature

CONSTRUCTION

- Powder coated, die-cast aluminum housing
- Frosted lens for diffuse lighting

APPLICATIONS

- Healthcare
- Hospitality
- Office
- Property Management
- Residential
- Retail

WARRANTY

- 5-Year limited warranty available [online](#). Contact your EiKO sales rep for additional details.

project name	type
catalog number	voltage
approved by	date



AVAILABLE MODELS

ORDER	ORDER CODE	ITEM #	SIZE	WATTS (W)	CCT (K)	LUMENS (LM)	LPW	VOLTS (V)	DIMMING	ENERGY STAR
	15371	DWR4-10W-830-D-WH	4"	10	3000	650	65	120	Triac	
	15382	DWR4-13W-830-D-WH	4"	13	3000	800	62	120	Triac	
	15372	DWR4-10W-8FCCT-D-WH	4"	10	2700/3000/3500/4000/5000	820	82	120	Triac	★
	15383	DWR4-PS13-8FCCT-D-WH	4"	13/9/7	2700/3000/3500/4000/5000	1,100/800/650	85	120	Triac	★
	15373	DWR6-12W-830-D-WH	6"	12	3000	800	67	120	Triac	
	15384	DWR6-15W-830-D-WH	6"	15	3000	1,100	73	120	Triac	
	15374	DWR6-13W-8FCCT-D-WH	6"	13	2700/3000/3500/4000/5000	1,100	85	120	Triac	★
	15385	DWR6-PS16-8FCCT-D-WH	6"	16/10/8	2700/3000/3500/4000/5000	1,600/1,100/800	100	120	Triac	★
	15375	DWR8-12W-830-D-WH	8"	12	3000	850	71	120	Triac	
	15377	DWR8-14W-830-D-WH	8"	14	3000	1,100	79	120	Triac	
	15376	DWR8-13W-8FCCT-D-WH	8"	13	2700/3000/3500/4000/5000	1,100	85	120	Triac	★
	15378	DWR8-PS18-8FCCT-D-WH	8"	18/12/9	2700/3000/3500/4000/5000	1,500/1,100/750	83	120	Triac	★

MODEL CONFIGURATOR										
MODEL	SIZE	-	WATTAGE	-	CRI	FIELD CCT	-	DIMMING	-	COLOR
DWR : Downlight Wafer Remote	4 - 4" 6 - 6" 8 - 8"	-	10W - 10W 12W - 12W 13W - 13W 14W - 14W PS13 - 13/9/7W PS16 - 16/10/8W PS18 - 18/12/9W	-	8 - 80+	30 - 3000K FCCT - 2700/3000/3500/4000/5000K	-	D - Dimming (Triac)	-	WH - White

PRODUCT DIMENSIONS

