

## LED T8 U-Bend Direct Fit Replacement Lamps



11.5  
watts

1,800  
lumens

156+  
lpw

universal  
burn

### Features

- Directly replaces fluorescent U-bend lamps
- No socket changes, uses shunted or non-shunted sockets
- Operates on most electronic T8 (instant & programmed) ballasts
- Instantaneous full light output upon power-up
- 4000K CCT
- NSF listed for commercial foodservice equipment
- Frosted glass lens reduces visual glare
- Environment-friendly, no mercury or lead
- 5 year product warranty
- Suitable for use in totally enclosed fixtures
- No rewiring or modifications of any kind required



### Performance

- 1800 lumens (@ 11.5W)
- 80 CRI
- THD: <20%
- Power Factor: 0.98
- Rated Lifetime: 50,000 hours (@ L70)
- UL listed for damp locations
- Suitable for use in fixtures where ambient temperature is between -4°F (-20°C) and 113°F (45°C)
- Does not operate on magnetic ballasts
- Does not operate on T12 ballasts
- Visit [eiko.com](http://eiko.com) to view complete ballast compatibility information

### Applications

- Highbays
- Troffers
- Industrial Strips
- Cove Lighting
- Warehouses
- Stairwells
- Cold Storage



## LED T8 U-Bend Direct Fit Replacement Lamps



NSF offers the most accepted and trusted certification and verification programs for commercial foodservice equipment, specified by health departments, restaurant buyers and specifiers worldwide. NSF means market access – products with the NSF mark receive guaranteed regulatory acceptance in North America and improved acceptance worldwide. Verification programs, such as HACCP Compliance Verification - EU, demonstrate hygienic quality, independently verified by a trusted source.

### Ordering Information

Order Code	Item #	Length	Lm	Nominal W	V (Ballast Dependent)	CCT	CRI	Glass Tube	Life/Hrs	DLC
<b>10093</b>	LED11.5WT8F/U6/835-G8DR	6" U-Bend	1,800	11.5W	120-277V, 347V	3500K	80+	Frosted	50K	✓
<b>10063</b>	LED11.5WT8F/U6/840-G8DR	6" U-Bend	1,800	11.5W	120-277V, 347V	4000K	80+	Frosted	50K	✓
<b>10068</b>	LED11.5WT8F/U6/850-G8DR	6" U-Bend	1,800	11.5W	120-277V, 347V	5000K	80+	Frosted	50K	✓

NOTE: Use order code when ordering.

✓ DesignLights Consortium® Qualified

watch > like > follow



23220 W. 84<sup>th</sup> St, Shawnee, KS 66227 · (P) 1.800.852.2217 · (F) 1.800.492.8975  
 Canada: 81 King St, Barrie, ON L4N 6B5 · (P) 1.888.410.8151 · (F) 1.888.705.1335