

LED T8 Direct Fit Replacement Lamps



10-15
watts

10-15
watts

1,450-
2,200
lumens

up to
150
lpw

Features

- Solid state direct replacement for 3' or 4' T8 linear fluorescent
- No socket changes, uses shunted or non-shunted sockets
- Operates on most electronic T8 (instant & programmed) ballasts
- Instantaneous full light output upon power-up
- Choice of 3500K, 4000K, or 5000K CCT
- NSF listed for commercial foodservice equipment
- Frosted glass lens reduces visual glare
- Environment-friendly, no mercury or lead
- 5 year product warranty
- Suitable for use in totally enclosed fixtures
- No rewiring or modifications of any kind required



Performance

- 3': 1,450 lumens @ 10W
- 4': 1,800 lumens @ 12W
- 4': 2,200 lumens @ 15W
- 80 CRI
- Beam Angle: 220°
- THD: <20%
- Power Factor: 0.98
- Rated Lifetime: 50,000 hours @ L70
- UL listed for damp locations
- Suitable for use in fixtures where ambient temperature is between -4°F (-20°C) and 113°F (45°C)
- Does not operate on magnetic ballasts
- Does not operate on T12 ballasts
- Operates on AC emergency ballasts as listed in ballast compatibility list
- Visit eiko.com to view complete ballast compatibility information

Applications

- Highbays
- Troffers
- Industrial Strips
- Cove Lighting
- Warehouses
- Stairwells
- Cold Storage



LED T8 Direct Fit Replacement Lamps

Photometrics



NSF offers the most accepted and trusted certification and verification programs for commercial foodservice equipment, specified by health departments, restaurant buyers and specifiers worldwide. NSF means market access – products with the NSF mark receive guaranteed regulatory acceptance in North America and improved acceptance worldwide. Verification programs, such as HACCP Compliance Verification - EU, demonstrate hygienic quality, independently verified by a trusted source.

Ordering Information

Order Code	Item #	Length	Lm	Nominal W	V (Ballast Dependent)	CCT	CRI	Glass Tube	Bm	Life/Hrs	DLC
10303	LED10WT8F/36/835-G8DR	3'	1,450	10W	120-277V, 347V	3500K	80+	Frosted	220°	50K	✓
10262	LED10WT8F/36/840-G8DR	3'	1,450	10W	120-277V, 347V	4000K	80+	Frosted	220°	50K	✓
10263	LED10WT8F/36/850-G8DR	3'	1,450	10W	120-277V, 347V	5000K	80+	Frosted	220°	50K	✓
09931	LED12WT8/48/835-G8DR	4'	1,700	12W	120-277V, 347V	3500K	80+	Frosted	220°	50K	✓
09932	LED12WT8/48/840-G8DR	4'	1,800	12W	120-277V, 347V	4000K	80+	Frosted	220°	50K	✓
09933	LED12WT8/48/850-G8DR	4'	1,800	12W	120-277V, 347V	5000K	80+	Frosted	220°	50K	✓
09934	LED15WT8/48/835-G8DR	4'	2,100	15W	120-277V, 347V	3500K	80+	Frosted	220°	50K	✓
09935	LED15WT8/48/840-G8DR	4'	2,200	15W	120-277V, 347V	4000K	80+	Frosted	220°	50K	✓
09936	LED15WT8/48/850-G8DR	4'	2,200	15W	120-277V, 347V	5000K	80+	Frosted	220°	50K	✓

NOTE: Use order code when ordering.

✓ DesignLights Consortium® Qualified

watch > like > follow



23220 W. 84th St, Shawnee, KS 66227 · (P) 1.800.852.2217 · (F) 1.800.492.8975
 Canada: 81 King St, Barrie, ON L4N 6B5 · (P) 1.888.410.8151 · (F) 1.888.705.1335