



JAVELIN : LED LINEAR RETROFIT

DESCRIPTION

The Javelin Series of retrofit kits provide an energy and cost efficient alternative to standard fluorescent tubes used in linear and troffer type fixtures. These sleek luminaires are designed for easy one-person installation. The retrofit kits come in 4' and 8' lengths, and range in power from 20W to 75W.

FEATURES

- Attractive modern designs
- Up to 40% savings over non-LED fixtures
- Programmable/dimming driver
- Easy, one-person installation

LISTINGS

- ETL Listed
- ROHS Compliant

PERFORMANCE

- Design life: 50,000 hours
- CCT: 3500K, 4000K, 5000K
- CRI: >80

ELECTRICAL

- Input voltage: 100-277V
- Power Factor: >.90
- THD: <20%

THERMAL

- Operating temperature: -40°F to 122°F (-40°C to 50°C)

CONSTRUCTION

- Painted steel

WARRANTY

- 5 year limited warranty; see eiko.com for warranty details

project name	type
catalog number	
comments	voltage
approved by	date



APPLICATIONS

- Commercial Buildings
- Government Buildings
- Production Areas
- Hospitals
- Malls
- Schools
- Offices
- Grocery Stores
- Hallways



ORDERING INFORMATION

EXAMPLE: XALRS4-0420W35K-BUYW

Model	Length	Wattage	CCT	CRI	Voltage	Dimming	W
XALRS4 : Linear Retrofit Strip	04 - 4' 08 - 8'	20 - 20W 40 - 40W 75 - 75W	35 - 3500K 40 - 4000K 50 - 5000K	B - >80	U - 100-277V	Y - 0-10V	W - White

PERFORMANCE SUMMARY

Item #	Retrofit or Fixture	Watts	Lumens	CCT	CRI	Volts	Length	Lens	Dimming
XALRS4-0420W35K-BUYW	Retrofit	20W	2,654	3500K	80+	100-277V	4'	White	0-10V
XALRS4-0420W40K-BUYW	Retrofit	20W	2,708	4000K	80+	100-277V	4'	White	0-10V
XALRS4-0420W50K-BUYW	Retrofit	20W	2,763	5000K	80+	100-277V	4'	White	0-10V
XALRS4-0440W35K-BUYW	Retrofit	40W	5,058	3500K	80+	100-277V	4'	White	0-10V
XALRS4-0440W40K-BUYW	Retrofit	40W	5,161	4000K	80+	100-277V	4'	White	0-10V
XALRS4-0440W50K-BUYW	Retrofit	40W	5,264	5000K	80+	100-277V	4'	White	0-10V
XALRS4-0840W35K-BUYW	Retrofit	40W	5,402	3500K	80+	100-277V	8'	White	0-10V
XALRS4-0840W40K-BUYW	Retrofit	40W	5,212	4000K	80+	100-277V	8'	White	0-10V
XALRS4-0840W50K-BUYW	Retrofit	40W	5,622	5000K	80+	100-277V	8'	White	0-10V
XALRS4-0875W35K-BUYW	Retrofit	75W	9,230	3500K	80+	100-277V	8'	White	0-10V
XALRS4-0875W40K-BUYW	Retrofit	75W	9,418	4000K	80+	100-277V	8'	White	0-10V
XALRS4-0875W50K-BUYW	Retrofit	75W	9,606	5000K	80+	100-277V	8'	White	0-10V

DIMENSIONS

Fixture	Length	Width	Height
4' Retrofit	47.88"	Adjustable 4.25" - 5.25"	3.13"
8' Retrofit	95.87"		



8' Retrofit



4' Retrofit