
FEATURES


- Wide forward throw distribution for even illumination of stairwells, hallways, and restrooms
- Full range dimming for optimization of occupied & unoccupied states
- Field programmable lighting controls
- Shallow profile for full ADA compliance
- · As low as 10% illumination in off state



TECHNICAL INFORMATION

- **LEDs**: Best efficacy of mid level power LEDs, 80+ CRI, Utilizes aluminum substrate to provide an advanced thermal management system.
- **Housing**: All aluminum construction minimizes weight and maximizes thermal performance of the LED light engine.
- Construction: Robust all aluminum chassis and components allow for maximum dissipation of heat and long life of electrical components.
- Reflector: Utilizing white optics high diffuse, high reflectance films.
 Maximize light reflection, output, and brightness
- Finish: All parts are coated with a gloss white paint to provide soft even illumination.

DIMENSIONAL INFORMATION















LS1 SERIES

ORDERING INFORMATION

 $Part \ Number = Style + Size + Light \ Engine + Color \ Temperature + Options \\ (Example: F-14LS1-L4M-50-FR = 1x4 LS1 \ Fixture \ with 26W, 5000K \ Color \ temperature \ and \ a \ Frosted \ Lens)$

STYLE	SIZE	LIGHT ENGINE	COLOR TEMP.	OPTIONS
F - Fixture	12LS1 - 1' X 2'	L2M - 2' - 10W - 905 LUMENS	35 - 3500K	FR - FROSTED LENS
	14LS1 - 1' X 4'	L2H - 2' - 16W - 1525 LUMENS	40 - 4000K	S1 - OCCUPANCY SENSOR
		L2V - 2' - 22W - 2100 LUMENS	50 - 5000K	EM5W - 5W EMERGENCY BALLAST
		L4M - 4' - 26W - 2500 LUMENS		EM7W - 7W EMERGENCY BALLAST (1X4 ONLY)
		L4H - 4' - 32W - 3060 LUMENS		EMIOW - 10W EMERGENCY BALLAST (1X4 ONLY)
		L4V - 4' - 39W - 3737 LUMENS		

Occupancy Sensor plus Daylight Harvesting On/Off Occupancy and Daylight with Optional Networked Lighting Controls Networked Lighting Controls Only Occupancy and Daylight with Hi/Lo/Off Occupancy and Daylight with Grouping (Alt: Occupancy Sharing) Dusk To Dawn On/Off







