

MUR Series - 150 Watts

Project: _____ Date: _____

Catalog #: _____

Notes: _____

Key Features & Benefits:

- Multiple Mounting Options Designed to Retrofit
 - Street Lights
 - High Bays / Low Bays
 - Garage Lights
 - Shoe Box Fixtures
 - Wall Packs
- Utilize Existing Fixture
- 10 Year Warranty
- Environmentally friendly
 - No mercury
 - No hazardous substances
 - Reduced energy consumption
- Optimized Pin Array Heatsink
- High Efficacy, Up to 133 lm/W
- Overheat Shutdown
- L70 Lifetime >100,000 Hours
- CRI >75



Technical Specifications:

Light Specifications

Lumen Output: Up to 19,940
 Efficacy (lm/W): Up to 133 Lumens per Watt
 Correlated Color Temperature (CCT): 3000K, 4000K, 5000K
 CRI: >75
 Rated Life (hrs): 100,000 Hours
 IES Classification: Fixture Dependant
 Dimensions (LxWxH): 8.6" x 5.7" x 2.5"
 External Driver Dimensions (LxWxH): 8.97" x 2.67" x 1.52"
 Weight Without Driver (lbs): 1.7

Driver Specifications

Power: 150 Watts
 Input Voltage: 120-277 VAC, 180-528 VAC
 Input Current @120V: 1.25A
 Input Current @277V: 0.54A
 Input Current @480V: 0.312A
 Power Factor: >0.95
 Total Harmonic Distortion (THD): <20%
 Operating Temperature: -40°C to +50°C (-40°F to +122°F)

Example Part Number: **ESL-MUR-150W-330**

ESL	-	MUR	-	150W	-	3	-	
ESL		TYPE		WATTS		GENERATION		COLOR
		MUR (Multi-Use Retrofit)		150W (150 Watts)		3 (Series 3)		30 (3000 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)
								VOLTAGE
								HV (180-528 VAC)

Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN	CRI	DLC QPL
ESL-MUR-150W-330	150	19,005	127	3000K	>75	N/A
ESL-MUR-150W-340	150	19,510	130	4000K	>75	PREMIUM PADDSX8S
ESL-MUR-150W-350	150	19,940	133	5000K	>75	PREMIUM PXWZ8WQD
ESL-MUR-150W-330-HV	150	19,005	127	3000K	>75	N/A
ESL-MUR-150W-340-HV	150	19,510	130	4000K	>75	PREMIUM PJTJMV3A
ESL-MUR-150W-350-HV	150	19,940	133	5000K	>75	PREMIUM P5CUQWCA

Dimensions:

