

Key Features & Benefits:

- Multiple Mounting Options Designed to Retrofit
 - Street Lights
 - High Bays / Low Bays
 - Garage Lights
 - Shoe Box Fixtures
 - Wall Packs
- Utilize Existing Fixture
- 10 Year Warranty
- Optimized Pin Array Heatsink
- Overheat Shutdown
- L70 Lifetime >100,000 Hours
- Intelligent Thermal Control
- Compatible with Networked Lighting Control Qualified Systems



Project: _____

Date: _____

Catalog #: _____

Notes: _____



Technical Specifications:

Light Specifications

Lumen Output: Up to 9,420 Lumens
 Efficacy (lm/W): Up to 126 Lumens per Watt
 Kelvin: 3000K, 4000K, 5000K
 CRI: >75
 Rated Life (hrs): 100,000 Hours
 IES Classification: Fixture Dependant
 Dimensions (LxWxH): 6.8" x 4.9" x 2.6"
 Weight Without Driver (lbs): 1.05

Driver Specifications

Power: 75 Watts
 Input Voltage: 120-277 VAC, 180-528 VAC
 Input Current @120V: 0.625A
 Input Current @277V: 0.27A
 Input Current @480V: 0.16A
 Operating Temperature: -40°F to 176°F (-40°C to 80°C)
 Non-Dimmable Driver Dimensions - (LxWxH): 7.3" x 2.5" x 1.6"
 0-10v Dimmable Driver Dimensions - (LxWxH): 7.7" x 2.4" x 1.53"

High Voltage Driver Dimensions - (LxWxH): 9.3" x 2.7" x 1.53"

0-10v Dimmable High Voltage Driver Dimensions - (LxWxH): 9.3" x 2.7" x 1.53"

Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN	CRI	DLC QPL
ESL-MUR-75W-330	75W	9,240	123	3000K	>75	N/A
ESL-MUR-75W-340	75W	9,360	125	4000K	>75	PREMIUM PVWHF7PQ
ESL-MUR-75W-350	75W	9,420	126	5000K	>75	PREMIUM P1JKA8C
ESL-MUR-75W-330-HV	75W	9,240	123	3000K	>75	N/A
ESL-MUR-75W-340-HV	75W	9,360	125	4000K	>75	PREMIUM P18HFJYG
ESL-MUR-75W-350-HV	75W	9,420	126	5000K	>75	PREMIUM P7VXZ239



Ordering Guide:

Example Part Number: **ESL-MUR-75W-330-HV-DD**

ESL	MUR	75W	3				
ESL	TYPE	WATTS	GENERATION	KELVIN	VOLTAGE*	DIMMING*	OPTIONS*
	MUR (Multi-Use Retrofit)	75W (75 Watts)	3 (3rd Generation)	30 (3000 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)	HV (180-528 VAC)	DD (0-10v Dimming)	

* Leave blank if HV, Dimming or Options are not needed

Options (Add as Suffix):

ESL-SP-277	Surge Protector, Up to 277 VAC Input
ESL-1OCC	On/Off High Bay Occupancy Sensor, 8' - 41' Mounting
ESL-2OCC	0-10v Dimming Sensor, 8' - 46' Mounting
ESL-3OCC	IP65 0-10v Dimming Sensor, 8' - 50' Mounting, Wire From Side
ESL-3OCCB	IP65 0-10v Dimming Sensor, 8' - 50' Mounting, Wire From Top
ESL-4OCC	Occupancy Sensor, 0-10v Dimming, 8'-20' Mounting
ESL-EMG-DC-8W	External Emergency Backup 850 Lumens (Field Remotely Installed)
ESL-EMG-AC-18W	External Emergency Backup 1,980 Lumens (Field Remotely Installed)
ESL-SPD-277-1	Hard Wire Surge Protector; (100-277 VAC) Max Discharge Current: 20kA
ESL-480V-SD01	480 Volt Step Down Transformer
ESL-REM-100	Hand Held Remote to Program ESL-3OCC
ESL-REM-101	Hand Held Remote to Program ESL-2OCC, ESL-4OCC

Dimensions:

